



IFIA Petroleum Inspector Certification Programme

Test Questions

English Language Eighth Edition February 2024

BLANK PAGE
(BACK OF COVER)

IFIA Petroleum Inspector Certification Programme

Test Questions

English Language Eighth Edition February 2024

Question updates since previous version (test question numbers adjusted for this document):

Revised: 1.13, 1.16, 1.28, 1.29, 1.34, 1.36, 2.07, 2.08, 2.20, 2.21, 2.23, 2.28, 2.35, 2.36, 3.15, 4.05, 4.08, 4.19, 4.25, 4.28, 4.63, 4.68, 4.87, 5.03, 5.27, 5.38, 5.56, 5.61, 5.68, 5.71, 5.82, 5.87, 5.89, 5.90, 6.01, 6.04, 6.05, 6.07, 6.16, 6.19, 6.20, 6.25, 6.26, 6.27, 6.31, 6.32, 6.39, 6.44, 6.45, 6.46, 6.69, 6.83, 7.07, 8.05, 8.07, 8.11, 8.12, 8.17, 8.22, 8.24, 8.25, 8.35, 8.50, 9.02, 10.20, 10.22 [10.26 and 10.27 moved to 4.92 and 4.93]

Removed (previous number): 4.54, 5.03, 5.73, 5.84, 6.39

Added: 6.87, 6.88, 7.58

Copyright © 2024 TIC Council

All rights reserved

No part of this document may be reproduced by any means, or transmitted or translated into a machine language without the written permission of TIC Council

Disclaimers

This document is designed to be used as part of the IFIA Petroleum Inspector Certification Programme. TIC Council makes no warranty, express or implied, that it is fit for any purpose whatsoever or to the absolute sufficiency of the material presented. It cannot be assumed that every procedure is covered.

TIC Council assumes no responsibility for any inaccuracies in reproduction or errors in interpretation of any authority. TIC Council reserves the right to modify or amend this document without prior notification but assumes no responsibility to update or issue corrections.

Reference is made in this document to the American Petroleum Institute's Manual of Petroleum Measurement Standards (API MPMS), to International Standards Organisation (ISO) documents and to the Energy Institute's Hydrocarbon Management (HM) documents (previously Institute of Petroleum Measurement Manual, IP PMM). These are copyright publications and questions or requests for information regarding these standards should be addressed to the respective organisation.

UK First Edition published February 2003

International First Edition published October 2004 (fully compatible)

International Second Edition published January 2008

International Third Edition published March 2009 (questions fully compatible)

International Fourth Edition published November 2012

Fifth Edition published April 2016

(replaces International Fourth Edition and Americas version Sixth Edition)

Sixth Edition published August 2016 – question 8.43 revised

Seventh Edition Published January 2020 – rebranded as TIC Council

Eighth Edition Published February 2024

Introduction

This document has been produced by the TIC Council Petroleum and Petrochemical Committee to represent a basic body of knowledge which is expected of a TIC Council member petroleum inspector. An examination must be passed in order to obtain the qualification “Certified Inspector of Petroleum” which will be comprised of a subset of 76 of the questions on this document (worth 1 point each). The examination will also include 8 unpublished scenario-based multiple-choice questions (worth 3 points each) representing real-life scenarios likely to be encountered when working in the field. The pass level is 75%.

Candidates must have completed a minimum of 6 months working as a petroleum inspector and a specified programme of field and classroom training. This is detailed in the TIC Council Petroleum Inspector Training Requirements List and must be fully documented in the employer’s internal training records.

The Petroleum Inspector Certification Programme is an international programme and the qualification is international and transferable.

The guidelines governing the Petroleum Inspector Certification Programme are determined by the TIC Council Petroleum and Petrochemical Committee.

The programme has been approved by US Customs and by Energy Institute committee representatives from a number of major oil companies and is recognised as key indicator of an inspector’s competence.

This eighth edition of the test questions includes metric and traditional units with alternate content in square brackets; []. Figures are **not** equivalent.

To obtain a copy of the guidelines or for any other enquiries concerning the programme please visit the website at www.tic-council.org. Further contact details are available there.

BLANK PAGE

Contents

Section 1	Calculations
Section 2	Definitions
Section 3	Loss Control
Section 4	Marine Measurement
Section 5	Safety
Section 6	Sampling
Section 7	Tank Gauging
Section 8	Temperature Determination
Section 9	Metering
Section 10	Ethics

BLANK PAGE

SECTION 1 – CALCULATIONS

- 1.01 As the density of a material increases, what happens to the API Gravity?**
- a. It becomes higher
 - * b. It becomes lower
 - c. It does not change
 - d. Answers a., b. and c. are all wrong
- 1.02 Density of any substance is the ratio of its mass to its volume, usually at a specified temperature. Relative Density is the ratio of the density of a substance at a specified temperature to the density of what other substance?**
- a. Pure ethanol at the specified temperature
 - b. Acetone at the specified temperature
 - * c. Pure water at the specified temperature
 - d. Vegetable oil at a specified temperature
- 1.03 When a capacity table indicates a reference API Gravity and an API Gravity correction per barrel variance for a shore tank, what data must be available to calculate a floating roof correction?**
- a. Weight of the roof only
 - b. API Gravity of the contents at 60 °F ; API Gravity for which the capacity table was calculated; correction in barrels for each degree of difference in API Gravity
 - c. Observed API Gravity of the contents; Weight of the roof; correction in barrels for each degree of difference in API Gravity
 - * d. Observed API Gravity of the contents; API Gravity for which the capacity table was calculated; correction in barrels for each degree of difference in API Gravity
- 1.04 When calculating the Gross Standard Volume (GSV) in a shore tank at a pressure of 1 atmosphere, the factor 'Ctpl' / 'CTL' is the same as which other factor?**
- a. Vessel Experience Factor (VEF)
 - * b. Volume Correction Factor (VCF)
 - c. Weight Correction Factor (WCF)
 - d. Voyage Analysis Report (VAR)

- 1.05** **If a cargo does not contain S&W, the Gross Standard Volume and the Net Standard Volume are the same.**
- * a. True
b. False
c.
d.
- 1.06** **For a crude oil cargo, what information does the formula $GOV \times VCF$ give?**
- * a. GSV (Gross Standard Volume)
b. NSV (Net Standard Volume)
c. TCV (Total Calculated Volume)
d. VCF (Volume Correction Factor)
- 1.07** **The Total Calculated Volume is equal to the Gross Standard Volume plus what?**
- * a. Free water
b. S&W
c. Roof Correction
d. Free Water and S&W
- 1.08** **For a trim correction to apply, which of the following conditions must exist?**
- a. Vessel must be down by the stern
b. Liquid may not contact the forward bulkhead
* c. Liquid must touch all four bulkheads
d. Conditions a., b. and c. must all exist
- 1.09** **What is the equation used to calculate a vessel's 'trim factor'?**
- * a. Trim divided by the length between perpendiculars
b. Trim divided by the vessel's width
c. Trim divided by the tank length
d. Tank length divided by the length between perpendiculars

- 1.10 What must roof corrections be based on?**
- * a. The density or API gravity at the observed temperature of the oil in the tank
 - b. The density or API gravity at standard temperature of the oil in the tank
 - c. The barrels per inch calculated from the tank capacity table
 - d. The critical zone
- 1.11 What is the 'trim factor' of a vessel?**
- a. The amount the vessel is trimmed
 - * b. The slope per linear foot (or metre) of the vessel
 - c. The slope per square foot (or metre) of the vessel
 - d. The length between perpendiculars times the trim
- 1.12 Tanks on barges or other small vessels do not require trim corrections because they are too small for a correction to make a significant difference.**
- a. True
 - * b. False
 - c.
 - d.
- 1.13 When an automatic in-line sampler is used correctly during the discharge of a crude oil vessel, what is the resulting sample likely to include?**
- a. Oil
 - b. Oil and sediment
 - * c. Oil, S&W & Free Water
 - d. S&W and Free Water only
- 1.14 A tank has a measured gauge height of 15.000 m [45'] and is filled to a 10.000 m [40'] innage with no free water. To take a middle spot sample, to what point in the tank must you lower the sampler?**
- a. 5.000 m [20'] below the reference gauge point
 - b. 7.500 m [22.5'] below the reference gauge point
 - * c. 10.000 m [25'] below the reference gauge point
 - d. 7.500 m [25'] from the tank bottom

- 1.15** A tank has a measured gauge height of 15.000 m [45'] and is filled to a 9.000 m [30'] innage with no free water. To take a lower spot sample, to what point in the tank must you lower the sampler?
- a. 3.000 m [10'] below the reference gauge point
 - b. 5.000 m [15'] above the tank bottom
 - c. 12.000 m [30'] below the reference gauge point
 - * d. 13.500 m [40'] below the reference gauge point
- 1.16** A tank has a measured gauge height of 15.000 m [45'] and is filled to a 9.000 m [30'] innage with no free water. To take an upper spot sample, to what point in the tank must you lower the sampler?
- a. 4.000 m [12'] above the tank bottom
 - * b. 7.500 m [20'] below the reference gauge point
 - c. 9.500 m [21'] below the reference gauge point
 - d. 6.000 m [15'] above the tank bottom
- 1.17** A tank has a measured gauge height of 15.000 m [45'] and is filled to a 12.000 m [40'] innage with no free water. To take a top spot sample to what point in the tank must you lower the sampler?
- a. 5.000 m [5' 00"] below the reference gauge point
 - * b. 3.150 m [5' 06"] below the reference gauge point
 - c. 9.000 m [11' 08"] below the reference gauge point
 - d. 0.150 m [12' 06"] below the reference gauge point
- 1.18** What is generally accepted as the density [API Gravity] of free water for cargo calculations?
- a. 60 kg/m³ [6]
 - * b. 1000 kg/m³ [10]
 - c. 14.5 kg/m³ [15]
 - d. 1.0 kg/m³ [1]
- 1.19** The term specific gravity has been replaced by what term?
- a. API gravity
 - b. Density in vacuum
 - * c. Relative density
 - d. Density in air

- 1.20** When a vessel's capacity tables are graduated to greater than 1/8", 0.01', or 3 mm, you should interpolate to calculate the volume at the gauged level in the tank.
- * a. True
 - b. False
 - c.
 - d.
- 1.21** Which API Chapter contains density/weight/volume conversion routines for cargo quantity calculations?
- * a. Chapter 11.5
 - b. Chapter 11.1
 - c. Chapter 12.1
 - d. Chapter 12.2
- 1.22** In what units is a metric tape graduated?
- * a. Millimeters
 - b. Feet
 - c. Hundredths of a foot
 - d. Inches
- 1.23** How many centimeters equal one inch?
- a. 3.16
 - b. 2.75
 - * c. 2.54
 - d. Answers a., b. and c. are all wrong
- 1.24** What term has been replaced by relative density?
- a. Density in vacuum
 - b. Density in air
 - * c. Specific gravity
 - d. Gravity by pyknometer
- 1.25** What is the formula to calculate API gravity at 60°F when relative density is known?
- a.
 - b.
 - c.
 - * d. $(141.5 \div \text{Relative Density @ } 60/60\text{F}) - 131.5$

- 1.26** **What is the equivalent of 0 degrees Celsius on the Fahrenheit scale?**
- a. 0 °F
 - b. 12 °F
 - c. 50 °F
 - * d. 32 °F
- 1.27** **Is the density used in the measurement calculations (API Ch 11.5) density in air or vacuum?**
- a. Air
 - * b. Vacuum
 - c.
 - d.
- 1.28** **A product has API gravity at 60°F of 21.3. What table would be used to find the equivalent density at 15 degrees Celsius?**
- a. API Ch 8.2 (Table 8)
 - b. API Ch 17.1 (Table 11)
 - * c. API Ch 11.5 (Table 3)
 - d. API Ch 11.1 (Table 6B)
- 1.29** **What table should be used to convert m3 at 15 °C to metric tons in air?**
- a. API Ch 8.2 (Table 8)
 - * b. API Ch 11.5 (Table 56)
 - c. API Ch 11.1 (Table 6B)
 - d. API Ch 11.6 (Table 13)
- 1.30** **A list correction is most similar to which of the following calculations?**
- a. A wedge formula
 - b. A vessel experience factor
 - c. A voyage ratio
 - * d. A trim correction

- 1.31** **The correction for the effect of temperature on the shell of a non-insulated shore tank should be calculated if the contents of the tank are at 15°C [60°F].**
- * a. True
 - b. False
 - c.
 - d.
- 1.32** **It is necessary to know the Vessel Experience Factor of a ship before you can accurately determine whether there has been a loss or gain of cargo in transit.**
- a. True
 - * b. False
 - c.
 - d.
- 1.33** **Which API MPMS Chapter or Energy Institute HM document contains guidelines for the calculation of oil quantities?**
- a. Chapter 3.1 / HM 4
 - b. Chapter 8.1 / IP 475
 - c. Chapter 17.11 / HM 52
 - * d. Chapter 12 / HM 1
- 1.34** **What table should be used to convert barrels at 60 °F to cubic metres at 15 °C?**
- a. API Ch 17.1 (Table 8.2)
 - * b. API Ch 11.5 (Table 52)
 - c. API Ch 17.1 (Table 6A)
 - d. API Ch 11.1 (Table 13)
- 1.35** **Who decides whether to apply a line displacement differential to a shore figure?**
- a. Customs
 - b. Inspection company personnel
 - * c. The Buyer and Seller or Terminal procedures
 - d. Either a. or c. can decide

1.36 What table should be used to convert barrels at 60°F to long tons?

- a. API Ch 8.2 (Table 8)
- * b. API Ch 11.5 (Table 11)
- c. API Ch 17.1 (Table 3)
- d. API Ch 11.1 (Table 6B)

1.37 Which API Chapter contains temperature/pressure volume correction factor routines for cargo quantity calculations?

- a. Chapter 11.5
- * b. Chapter 11.1
- c. Chapter 12.1
- d. Chapter 12.2

SECTION 2 – DEFINITIONS

2.01 What does the API Gravity scale indicate?

- * a. Density
- b. Volume
- c. Weight in Vacuum
- d. Ratio of weight to density

2.02 What is a hydrometer?

- a. A device to measure viscosity
- b. A device to measure hydration
- * c. A device to measure density
- d. A device to measure water flow

2.03 What is ballast?

- a. Water in the tanks of a vessel used for laundry and other sanitation purposes
- b. Any water on board a vessel in any tank
- c. Water that is used to clean cargo tanks
- * d. Water that allows the vessel to maintain stability and to control stress and trim

2.04 What is a permanent ballast tank?

- a. A tank that contains ballast at all times
- * b. A tank that is designated to contain only ballast
- c. A tank that is used only to maintain a permanent list condition
- d. Answers a., b. and c. are all wrong

2.05 What does the abbreviation S&W stand for?

- a. Sand and Water
- b. Sediment and Waste
- c. Scale and Water
- * d. Sediment and Water

- 2.06 Which of the following are equivalent to a volume of one cubic metre?**
- a. 264.172 US gallons
 - b. 6.28981 US Barrels
 - c. 1000 litres
 - * d. Answers a., b. and c. are all correct
- 2.07 What is a Bill of Lading?**
- a. A receipt for the cargo
 - b. Evidence of the contract between a carrier and a shipper
 - c. A document confirming ownership of cargo
 - * d. Answers a., b. and c. are all correct
- 2.08 What is clingage?**
- a. The wedge shaped volume of oil remaining in a tank after discharge
 - b. The non-liquid wedge-shaped volume of oil remaining in a tank after discharge
 - * c. The cargo that adheres to the internal vertical surfaces of a tank after it has been emptied.
 - d. The ability of a liquid to cling to the bottom of a container
- 2.09 What is a datum plate?**
- * a. A level metal plate located directly under the reference gauge point to provide a fixed contact surface from which liquid depth measurement can be made.
 - b. A metal plate located next to the gauging point on a tank indicating the reference gauge height.
 - c. A metal plate located close to the gauging point on a tank listing all the relevant tank data
 - d. A level metal plate located at the top of a gauge hatch on a tank from which the gauge height is measured.

- 2.10 What is deadwood?**
- a. Wooden cup-case thermometer cases that are no longer fit for use
 - b. Any piece of gauging equipment made of wood (i.e. wooden handles of gauge tapes, cup-case thermometer cases) that have been exposed to chemicals and have been damaged as a result
 - * c. Any tank fitting or structural member inside a tank that affects the capacity of the tank
 - d. Answers a., b. and c. are all wrong
- 2.11 What is the formula for density?**
- a. Length divided by width
 - b. Volume divided by temperature
 - * c. Mass divided by volume
 - d. Mass divided by relative density
- 2.12 The density of a liquid will change as its temperature changes.**
- * a. True
 - b. False
 - c.
 - d.
- 2.13 What is relative density?**
- * a. The ratio of the mass of a given volume of liquid at a stated temperature to the mass of an equal volume of pure water at a stated temperature
 - b. The relative ability of a liquid to remain in a liquid state when cooled below standard freeze point
 - c. A measure of the relative viscosity of a liquid
 - d. The ratio of a given mass of a liquid when compared with its mass at 60 °F

2.14 What is an emulsion?

- a. A heavy viscous liquid
- b. A heavy viscous liquid containing a large amount of entrained sediment
- * c. An oil & water mixture that does not readily separate
- d. A layer of free water located above a heavy viscous petroleum product

2.15 What is Total Observed Volume (TOV)?

- * a. The total measured volume of all petroleum liquids, sediment and water, and free water at observed temperature
- b. The total measured volume of all petroleum liquids, sediment and water but excluding free water, at observed temperature
- c. The total volume of all petroleum liquids and sediment and water, corrected to a standard temperature by the appropriate volume correction factor for the observed temperature and density
- d. The total measured volume of all petroleum liquids excluding water and sediment, at observed temperature

2.16 What is Gross Observed Volume (GOV)?

- a. The total measured volume of all petroleum liquids, sediment and water, and free water at observed temperature
- * b. The total volume of all petroleum liquids and sediment and water, excluding free water, at observed temperature
- c. The total volume of all petroleum liquids excluding sediment and water and free water, at observed temperature
- d. The total volume of all petroleum liquids and sediment and water, excluding free water, corrected to a standard temperature by the appropriate volume correction factor for the observed temperature and density

2.17**What is Gross Standard Volume (GSV)?**

- a. The total volume of all petroleum liquids excluding free water, water and sediment, corrected to a standard temperature by the appropriate volume correction factor for the observed temperature and density
- b. The total volume of all petroleum liquids including free water, water and sediment, corrected to a standard temperature by the appropriate volume correction factor for the observed temperature and density
- * c. The total volume of all petroleum liquids and sediment and water, excluding free water, corrected to a standard temperature by the appropriate volume correction factor for the observed temperature and density
- d. The total volume of all petroleum liquids including free water but excluding sediment and water, corrected to a standard temperature by the appropriate volume correction factor for the observed temperature and density

2.18**What is Net Standard Volume (NSV)?**

- * a. The total volume of all petroleum liquids, excluding sediment and water and free water, corrected to a standard temperature by the appropriate volume correction factor for the observed temperature and density
- b. The total volume of all petroleum liquids, excluding sediment and water, but including free water, corrected to a standard temperature by the appropriate volume correction factor for the observed temperature and density
- c. The total volume of all petroleum liquids and free water, excluding sediment and water, corrected to a standard temperature by the appropriate volume correction factor for the observed temperature and density
- d. The total volume of all petroleum liquids and sediment and water and free water, corrected to a standard temperature by the appropriate volume correction factor for the observed temperature and density

2.19 What is Total Calculated Volume (TCV)?

- * a. GSV plus free water
- b. NSV plus free water
- c. GSV less sediment and water
- d. NSV plus sediment and water

2.20 How is an all levels sample obtained?

- a. By submerging an unstoppered sampler to a point near the tank draw-off outlet (suction) level and then raising it, all at a uniform rate, so that it is no less than 70% full on emerging from the liquid.
- b. By blending upper, middle and lower samples from the same tank.
- * c. By lowering the stoppered device to the bottom of the outlet suction level, but always above any free water, then opening the sampler and raising it at a uniform rate such that it is between 70% and 85% full when withdrawn from the product
- d. By submerging a stoppered sampler to the mid point of the product in a tank, then opening the sampler and raising and lowering it at a uniform rate until the sampler is full.

2.21 How is a running sample obtained?

- * a. by lowering an open (un-stoppered) sampling device to the bottom of the outlet suction level, but always above any free water, and returning it to the top of the product at a uniform rate such that the sampling device is between 70% and 85% full when withdrawn from the product
- b. by lowering a stoppered sampler to the level of the outlet, then opening the sampler and raising it at a uniform rate so that it is about 80% full when withdrawn from the oil
- c. by lowering a stoppered sampler to the mid point of the tank contents, then opening the sampler and raising and lowering it at a uniform rate until it is full
- d. by lowering an unstoppered sampler to the mid point of the tank contents, then raising and lowering it at a uniform rate until it is full

- 2.22 What is a floating roof tank?**
- a. A tank in which the roof floats freely on the surface of the liquid contents at all levels.
 - * b. A tank in which the roof floats freely on the surface of the liquid contents except at low levels when the weight of the roof is supported by its legs.
 - c. A tank in which the roof, supported by guide wires, can be adjusted to the required height for safe filling of the tank
 - d. Answers a., b. and c. are all wrong
- 2.23 What is the volume of all material in a tank at the observed temperature called?**
- a. Total Calculated Volume (TCV)
 - * b. Total Observed Volume (TOV)
 - c. On Board Quantity (OBQ)
 - d. Gross Observed Volume (GOV)
- 2.24 What is the volume of all material in a tank at the observed temperature less the free water called?**
- a. Total Observed Volume (TOV)
 - b. Gross Standard Volume (GSV)
 - * c. Gross Observed Volume (GOV)
 - d. Remaining On Board (ROB)
- 2.25 What is term for the total volume of liquid in a tank, less the free water, when corrected by the volume correction factor?**
- * a. Gross Standard Volume (GSV)
 - b. Gross Observed Volume (GOV)
 - c. Total Calculated Volume (TCV)
 - d. Net Standard Volume (NSV)

- 2.26 The Net Standard Volume (NSV) is the Gross Standard Volume (GSV) less?**
- a. Total Calculated Volume (TCV)
 - b. Total Observed Volume (TOV)
 - c. Gross Standard Volume (GSV)
 - * d. Sediment and Water (S&W)
- 2.27 What is the Reference Gauge Height of a tank?**
- a. The distance from the tank top to the tank bottom
 - b. The distance from the ullage hatch to the datum plate
 - * c. The distance from reference gauge point to the tank bottom or datum plate
 - d. The distance from tank bottom to the ullage hatch
- 2.28 What term describes a vessel with the forward draft greater than the aft draft?**
- a. Trimmed by the stern
 - * b. Trimmed by the head
 - c. Up at the bow
 - d. Listing dangerously
- 2.29 What does an innage, sounding or dip measure?**
- a. The depth of the empty space above the liquid in a tank
 - b. The depth of the sediment in a tank
 - c. The length of an innage tape
 - * d. The depth of the liquid in a tank
- 2.30 What is ullage?**
- * a. The depth of the empty space above the liquid in a tank
 - b. The height of the free water in a tank
 - c. The length of an ullage tape
 - d. The depth of the liquid in a tank

- 2.31** **What is the term for the amount to be paid by the Charterer if a vessel is delayed beyond the terms allowed in the Charter Party?**
- a. Dispatch money
 - * b. Demurrage
 - c. Disbursement
 - d. Penalty money
- 2.32** **What is the name of the document which is given as an official receipt for the cargo on board a vessel?**
- a. Certificate of Quality
 - b. Custom declaration
 - * c. Bill of Lading
 - d. Charter party
- 2.33** **What is the name given to the factor calculated from the ratios of historical Total Calculated Volumes (TCV) of a vessel (less OBQ/ROB) with the corresponding historical Total Calculated Volumes (TCV) of shore delivered/received volumes?**
- a. Voyage Analysis Factor
 - b. Tank Correction Factor
 - * c. Vessel Experience Factor
 - d. Ullage Correction Factor
- 2.34** **What is the name given to the mixture of oil, tank washings, water and sediment collected in a designated ship's tank?**
- a. Polluted oil
 - b. Merchantable oil
 - * c. Slops
 - d. Hazardous waste

- 2.35 What is the Total Observed Volume (TOV) defined as?**
- a. The volume read from the strapping table corrected to reference temperature
 - * b. The total measured volume of all petroleum liquids, sediment and water, and free water at observed temperature and pressure
 - c. The volume read from the strapping table corrected for roof displacement
 - d. The volume used to calculate a Vessel Experience Factor (VEF)
-
- 2.36 How is Gross Observed Volume (GOV) defined?**
- a. The volume read from the strapping table corrected to reference temperature
 - * b. The total volume of all petroleum liquids and sediment and water, excluding free water, at observed temperature and pressure
 - c. The volume read from the strapping table corrected for roof displacement
 - d. The volume used to calculate vessel ratios
-
- 2.37 How is 'draft' defined?**
- * a. The vertical distance from the surface of the water to the keel of the ship
 - b. The vertical distance from the deck of the ship to the surface of the water
 - c. The vertical distance from the Plimsoll mark to the bottom of the ship
 - d. The vertical distance from the Plimsoll mark to the deck
-
- 2.38 How is 'trim' defined?**
- a. The same as the draft
 - * b. The difference between the forward and aft draft
 - c. The average of the forward draft, the amidships draft, and the aft draft
 - d. The leaning of the vessel to one side

- 2.39** **How is 'list' defined?**
- a. The difference between the starboard draft and the port freeboard
 - * b. The leaning or inclination of a vessel expressed in degrees to port or starboard
 - c. The average of the starboard draft and the port draft expressed in degrees port or starboard
 - d. The difference between the forward and aft draft
- 2.40** **How is 'free water' defined?**
- * a. The layer of water present in the tank that is not suspended in the oil
 - b. Any water found on the bob with water paste
 - c. Any water found using the tank gauging equipment
 - d. Any water that is trim corrected
- 2.41** **What has the same meaning as the term 'innage'?**
- a. Ullage
 - * b. Sounding
 - c. Outage
 - d. Answers a., b. and c. are all wrong
- 2.42** **What is 'load on top'?**
- a. The shipboard practice of collecting water and water and oil mixtures resulting from ballasting and tank cleaning operations (usually in a slop tank) and subsequently loading cargo on top of it and pumping the mixture ashore at the discharge port.
 - b. The act of commingling existing onboard quantity with cargo being loaded
 - * c. Answers a. and b. are correct
 - d. Answers a., b. and c. are all wrong

2.43**What is a 'wall wash'?**

- * a. The activity of washing selected areas of a tank with a designated wash liquid and collecting the wash liquid for subsequent testing.
- b. The activity of rinsing a tank with clean, fresh water following tank cleaning to ensure that the product to be loaded will not be contaminated
- c. The activity of washing the walls of a tank to remove all traces of the product previously contained in the tank
- d. Answers a., b. and c. are all wrong

2.44**A US barrel has a volume of?**

- a. 55 US gallons
- b. 1 cubic meter
- c. 5 liters
- * d. 42 US gallons

SECTION 3 - LOSS CONTROL

- 3.01 Which API MPMS chapter provides guidelines for identifying the source of free water?**
- a. Chapter 8.3
 - b. Chapter 15
 - c. Chapter 17.2A
 - * d. Chapter 17.3
- 3.02 For the purposes of voyage analysis, what is a 'simple voyage'?**
- * a. A voyage from one load port to one discharge port with one cargo
 - b. A voyage from one load port to one discharge port with any number of cargoes
 - c. A voyage where all measurements were taken with automatic equipment only
 - d. A voyage that relied on carefully proved meters at both the load port and the discharge port
- 3.03 A volumetric loss is usually determined by comparing the discharge port outturn quantity to the load port Bill of Lading quantity. On a crude oil cargo, which volume is compared?**
- * a. TCV (Total Calculated Volume)
 - b. TOV (Total Observed Volume)
 - c. GOV (Gross Observed Volume)
 - d. Answers a., b. and c. are all wrong
- 3.04 After deducting the OBQ or ROB, which volume is used to calculate a vessel experience factor [VEF]?**
- * a. TCV (Total Calculated Volume)
 - b. TOV (Total Observed Volume)
 - c. GSV (Gross Standard Volume)
 - d. GOV (Gross Observed Volume)

- 3.05 What is the primary function of a Voyage Analysis Report (VAR)?**
- a. Providing a method for adjusting vessel figures for the Vessel Experience Factor (VEF)
 - * b. Systematically placing all data required for voyage analysis on one page
 - c. Convincing shippers that the Bill of Lading is overstated
 - d. Convincing receivers that there was a problem in the terminal that caused part of the cargo to be incorrectly measured
- 3.06 Which of the following steps is not included in the basic voyage analysis process?**
- a. Comparing Bill of Lading figures to outturn figures
 - b. Comparing vessel sailing figures to vessel arrival figures
 - c. Comparing ROB to OBQ
 - * d. Comparing line fill at load port to line fill at discharge port
- 3.07 For what purpose is a Letter of Protest issued to a terminal or vessel?**
- a. To inform the terminal / vessel that the operation was not carried out correctly
 - b. To allow the terminal or vessel to respond to a complaint
 - * c. To formally note that a situation has occurred which may require intervention from the client(s)
 - d. To give the terminal and vessel time to improve their operations before the next cargo movement
- 3.08 The difference between shore quantity and vessel quantity corrected by the VEF can indicate the likelihood of an inaccurate shore or vessel quantity.**
- * a. True
 - b. False
 - c.
 - d.

- 3.09** **What will a comparison of a vessel's departure Total Calculated Volume (TCV) and its arrival Total Calculated Volume (TCV) give an indication of?**
- a. Discharge performance
 - b. VEF accuracy
 - * c. In transit difference
 - d. Ballast water quantity
- 3.10** **Volumetric shrinkage occurs when light hydrocarbons are mixed with crude oils. Which API MPMS chapter covers the subject of volumetric shrinkage?**
- a. Chapter 9.3
 - b. Chapter 12.1
 - c. Chapter 12.2
 - * d. Chapter 12.3
- 3.11** **A shore pipeline is partially full before discharge and completely full after discharge. If the line content is not accounted for this will result in?**
- a. An apparent outturn gain as measured in the shore tank
 - * b. An apparent outturn loss as measured in the shore tank
 - c. An apparent loss of product as measured on the vessel
 - d. It will have no impact on the outturn
- 3.12** **Volumetric shrinkage is least when there is a large density difference between the two crude oils that are mixed.**
- a. True
 - * b. False
 - c.
 - d.

- 3.13 Which factors contribute to high evaporative losses?**
- a. High vapour pressure of the cargo
 - b. Excessive agitation of cargo during voyage
 - c. Gauge hatches left open
 - * d. Answers a., b. and c. are all correct
- 3.14 Metered quantities are always more accurate than those obtained from static shore tank measurements.**
- a. True
 - * b. False
 - c.
 - d.
- 3.15 Whether a shoreline is full, partly full or empty can affect accurate measurement of transferred volumes. Which documents provide guidelines for determining the fullness of pipelines between vessels and shore tanks?**
- * a. EI HM 70 / API MPMS Chapter 17.6
 - b. EI HM 21
 - c. EI HM 28
 - d. ISO 3171 / API MPMS Chapter 8.2
- 3.16 What is an 'in transit' difference?**
- * a. The difference between the vessel-measured volume at the load port and the vessel-measured volume at the discharge port
 - b. The difference between the vessel-measured volume at the load port and the shore-measured volume at the load port
 - c. The difference between the vessel-measured volume at the load port and the shore-measured volume at the discharge port
 - d. The difference between the shore line agreed tolerance at the load port and the shore line agreed tolerance at the discharge port

SECTION 4 - MARINE MEASUREMENT

- 4.01** **If the vessel incurs an in transit loss of product and an in transit gain in water, what action should be taken?**
- a. Obtain samples of the free water
 - b. Check the vessel's bunkers and bunker consumption during the voyage
 - c. Verify the condition of seals on the sea suction and overboard discharge valves
 - * d. Answers a., b. and c. are all correct
- 4.02** **If the vessel has independently certified wedge tables, they may be used instead of calculating the wedge volume yourself.**
- * a. True
 - b. False
 - c.
 - d.
- 4.03** **If a vessel is out of trim and product in a tank is touching all four bulkheads, should you use the wedge formula to calculate the volume?**
- a. Yes
 - * b. No
 - c.
 - d.
- 4.04** **Can a free water volume be calculated using a wedge formula, if the water does not touch the forward bulkhead.**
- * a. Yes
 - b. No
 - c.
 - d.

- 4.05 The preferred device for taking temperatures in a marine custody transfer is?**
- a. A liquid-in-glass thermometer in a cup-case assembly
 - b. An in-line temperature probe
 - c. An on-board radar system
 - * d. A portable electronic gauging device
- 4.06 What is the first thing you must do when you board a marine vessel?**
- * a. Report to the person in charge
 - b. Have the tanks open, ready to gauge and sample
 - c. Always take samples first
 - d. Always take gauges first
- 4.07 The vessel's master states that he will load 15,000 MT of a product. Your instructions state that a maximum of 13,000 MT should be loaded. What will be your course of action?**
- a. Assume the vessel's master has more up to date information
 - * b. Contact your principal for instructions.
 - c. Help to calculate the stop gauge to be certain the ship is not overloaded.
 - d. Leave the decision to the terminal.
- 4.08 When on board a marine vessel, responsibility for the inspector's personal protective equipment (PPE), the use of appropriate measurement equipment and the correct sampling equipment rests with?**
- * a. The inspector
 - b. The inspection company that the inspector works for
 - c. The vessel
 - d. The inspection company's principal

- 4.09 The term 'simultaneous ballasting or deballasting' means?**
- a. The vessel is transferring ballast from one ballast tank to another
 - b. The vessel is taking on or pumping off ballast in more than one tank at a time
 - * c. The vessel is transferring ballast while cargo is being pumped
 - d. The Chief Officer has been authorized to pump ballast ashore
- 4.10 Once sea valves are sealed by an independent inspector, the vessel staff should inform the inspector if those valves are operated during custody transfer.**
- * a. True
 - b. False
 - c.
 - d.
- 4.11 Why is measurement of free water on board marine vessels important?**
- a. To enable net cargo reconciliation
 - b. As a check against water quantities received at the shore terminal
 - c. As an indication of possible cargo theft
 - * d. Answers a., b. and c. are all correct
- 4.12 When you board a vessel, what is the first thing you do?**
- a. Start sampling
 - b. Check to see if the inert gas system is on
 - * c. Report to the person in charge on the vessel
 - d. Start taking temperatures

- 4.13 What is the purpose of ballast?**
- a. To keep the cargo warm
 - b. To segregate cargoes
 - c. To reduce the ship's fuel consumption
 - * d. To maintain the vessel's stability, trim and draft, and to control vessel stress
- 4.14 When should a bunker inspection be performed?**
- a. Only with fuel oil cargoes
 - b. With every product except gasoline
 - c. When requested by the vessel
 - * d. As appropriate or on the request of the principal
- 4.15 It is important when measuring ROB and OBQ to remember that?**
- a. Liquid material is usually ullaged.
 - b. Non-liquid material must be innaged.
 - * c. Vessel trim will have an effect on liquid quantities
 - d. Answers a., b. and c. are all correct
- 4.16 When is an OBQ inspection performed?**
- a. Before loading a clean product
 - * b. Before any cargo is loaded
 - c. Before any chemical is loaded
 - d. Before loading a clean product after a dirty one
- 4.17 It has been determined that ROB material is non-liquid and can only be measured from one gauge point. In order to calculate the volume of ROB, it should be assumed that the ROB is lying evenly across the bottom of the tank.**
- * a. True
 - b. False
 - c.
 - d.

- 4.18** **Why may multipoint gauging be required when performing an OBQ/ROB survey?**
- a. To help determine if a wedge condition exists
 - b. To help determine the nature (liquid or non-liquid) and quantity of the OBQ/ROB
 - c. Because the vessel is on even keel.
 - * d. Answers a. and b. are correct
- 4.19** **If multipoint innage measurements indicates that the non-liquid ROB/OBQ lies evenly across the bottom, how should you determine the volume as per API MPMS Chapter 17.4?**
- a. By use of trim corrections
 - b. By applying the wedge formula
 - * c. By using an average of the innage measurements.
 - d. By using the innage at the official gauge point
- 4.20** **Is it correct to apply a wedge calculation to an OBQ/ROB volume if the material is touching all four tank bulkheads ?**
- * a. No
 - b. Yes
 - c.
 - d.
- 4.21** **If you are only able to gauge the vessel's tanks from one location and the ROB is non-liquid, what should you use to obtain a volume?**
- a. A wedge table or formula
 - b. A trim corrected innage
 - * c. An uncorrected innage
 - d. A trim corrected ullage
- 4.22** **The On Board Quantity (OBQ) measured at a loading port will usually be greater than the remaining on board (ROB) measured at the previous discharge port.**
- * a. True
 - b. False
 - c.
 - d.

- 4.23 In what case will non-liquid ROB be considered not to be evenly distributed across the tank bottom?**
- a. When the vessel is listing
 - b. When the cargo was heated
 - * c. When multiple gauges in the tank prove otherwise
 - d. When ROB is more than 10cm [4"] deep
- 4.24 What components may be included in OBQ?**
- a. Free water
 - b. Non-liquid material
 - c. Liquid material
 - * d. Any combination of the above
- 4.25 What is cargo that adheres to the internal structure of a tank called?**
- a. Slops
 - * b. Clingage
 - c. Coatage
 - d. Ballast
- 4.26 What is the amount of material found in a tank prior to loading called?**
- a. Slops
 - * b. On Board Quantity (OBQ)
 - c. Bunkers
 - d. Remaining On Board (ROB)
- 4.27 What is the amount of material found in a tank after discharge called?**
- a. Slops
 - b. On Board Quantity (OBQ)
 - c. Bunkers
 - * d. Remaining On Board (ROB)

- 4.28** If the Master refuses to allow manual vessel measurements to be taken in accordance with inspection instructions , what should the inspector do?
- a. Contact the principals immediately
 - b. Issue a letter of protest to the vessel
 - c. Comply with the Master's instructions
 - * d. Answers a., b. and c. are all correct
- 4.29** If possible, should you seal a vessel's cargo system sea-valves or any equivalent connection to the ballast system prior to loading?
- a. No
 - * b. Yes
 - c.
 - d.
- 4.30** When portable electronic gauging equipment is used on board a marine vessel, which of the following considerations needs to be addressed?
- a. The equipment used must securely fit the vapour control valve.
 - b. The vessel's tank capacity tables must have been adjusted to accommodate the vapour control valve location and reference height
 - c. The equipment should be grounded
 - * d. Answers a., b. and c. are all correct
- 4.31** If there is spotting of the water paste above the clear cut level what would you use to calculate the volume?
- a. The very top of the spotting
 - * b. The clear cut but note the spotting height in the remarks
 - c. There is no mention of spotting in published standards
 - d. Answers a., b. and c. are all wrong

- 4.32** **If a vessel is being gauged in a swell the minimum number of dips per tank should be?**
- a. One
 - b. As many as necessary until two identical readings are obtained
 - c. Three and then averaged
 - * d. At least five, taken over the period of the motion, recorded and then averaged
- 4.33** **If the vessel is at a berth and rolling so that the cargo in the tank is moving more than 3 mm [1/8"], the minimum number of gauges to be taken is?**
- a. One
 - b. Two
 - c. Three
 - * d. Five
- 4.34** **In API MPMS Chapter 17.2 are there any guidelines for vessel inspection in adverse weather?**
- * a. Yes
 - b. No
 - c.
 - d.
- 4.35** **API MPMS Chapter 17.4/ISO 8697 does not address the issue of pumpability.**
- * a. True
 - b. False
 - c.
 - d.
- 4.36** **What term is used for the measurement of cargo through two or more openings in a tank?**
- a. Repetitive motion gauging
 - b. Duplicate gauging
 - * c. Multi-point gauging
 - d. Hatch survey

- 4.37 What is a Charter Party?**
- a. A traditional event hosted by the owner of a vessel celebrating the vessel being hired
 - b. A document specifying the dimensions of a vessel so it can get into the docks to load and unload its cargo
 - * c. A document outlining the terms and conditions that will apply to the owner and the charterer while a vessel is on hire
 - d. A statement of the demurrage to be charged to the charterer
- 4.38 What is the Reference Gauge Height of a vessel tank?**
- a. The overall height of the expansion trunk, referred to in the drawings
 - * b. The distance from the tank bottom to the reference gauge point as specified on the tank's capacity table
 - c. The measured distance from the tank bottom to the reference gauge point
 - d. The place inside the tank where automatic measurement floats are installed
- 4.39 As a minimum, how many liquid level measurements must be taken in a vessel's tanks when the vessel is in motion (rolling)?**
- a. 2
 - b. 3
 - c. 4
 - * d. 5
- 4.40 Is the holding of a key meeting prior to an inspection required to comply with Industry Standards**
- * a. Yes
 - b. No
 - c.
 - d.

- 4.41** According to EI HM28 [API 17.1], is the inspector required to be present at a key meeting prior to an inspection?
- * a. Yes
 - b. No
 - c.
 - d.
- 4.42** What is meant by the term 'trimmed by the head'?
- a. The aft draft reading is greater than the forward draft reading.
 - * b. The forward draft reading is greater than the aft draft reading.
 - c. The ship has water in the forepeak tank.
 - d. Trim corrections will always be added to the measured gauge
- 4.43** What is meant by the term 'trimmed by the stern'?
- * a. The aft draft reading is greater than the forward draft reading
 - b. The forward draft reading is greater than the aft draft reading.
 - c. The ship has water in the aft peak tank.
 - d. Trim corrections will always be subtracted from the measured gauge
- 4.44** What is the main reason for taking draft readings on fully-loaded vessels at the loading port?
- a. To be used at the discharge port in case of a cargo variance
 - * b. To enable calculation of trim or list corrections if needed
 - c. To compare with draft readings at the discharge port
 - d. To ensure adequate cargo drainage
- 4.45** What should trim corrections be applied to?
- a. Only the ROB quantity
 - b. Only the OBQ quantity
 - c. Any liquid material
 - * d. Any liquid material that is touching all four tank bulkheads

- 4.46** **What is the most accurate way of determining a vessel's list?**
- a. Ask the Chief Officer
 - b. Reading the clinometer
 - c. By comparing the port and starboard amidships draft marks
 - * d. Answers b. and c. are correct
- 4.47** **When a vessel is upright but not on an even keel, what should be used to correct tank dips/gauges?**
- a. Volume correction tables or volume correction calculations
 - * b. Trim correction tables or trim calculations
 - c. Weight correction tables or weight correction calculations
 - d. Draft correction tables or draft correction calculations
- 4.48** **The trim of a vessel will have no effect on the detection of free water.**
- a. True
 - * b. False
 - c.
 - d.
- 4.49** **In what circumstances will a wedge condition exist?**
- a. If liquid covers the bottom of the tank.
 - * b. If liquid does not touch all four bulkheads
 - c. If liquid accumulates beneath the gauge hatch
 - d. Answers a., b. and c. are all correct
- 4.50** **When non-liquid material covers the whole bottom of a tank, trim corrections are applicable.**
- a. True
 - * b. False
 - c.
 - d.

4.51 Which of the following conditions must be present for trim corrections to apply?

- * a. Tank contents must touch all four bulkheads
- b. Tank contents must be non liquid
- c. Tank contents must not contact the forward bulkhead
- d. Answers a. and b. are correct

4.52 What is the definition of 'list'?

- a. A piece of paper showing the names of all on board personnel
- * b. The inclination or leaning of the vessel away from the upright
- c. The correction required when the vessel is not on even keel
- d. The position of the tank contents when the vessel is down by the head

4.53 When should a wedge formula calculation be used on a vessel trimmed by the stern?

- * a. When liquid material does not contact the forward bulkhead
- b. When solid material is gauged at a single gauge point
- c. When free water completely covers the tank bottom
- d. Answers a., b. and c. are all correct

4.54 What is the preferred method for preparing composite samples from vessel tanks?

- a. On board as long as every cargo tank contains the same cargo
- b. On board, using equal volumes from each tank
- * c. In a laboratory, in proportion to the volume in each tank
- d. In a laboratory when S&W and API Gravity are the only tests needed

- 4.55** **What is 'freeboard' on a vessel?**
- * a. The distance from the waterline to the vessel's deck level
 - b. The distance from the waterline to the vessel's keel
 - c. The time when local Customs officials permit others to board the vessel
 - d. The time of day that lay time begins according to the Charter Party
- 4.56** **Using the Imperial system of measurement; what size are draft mark numbers?**
- a. 12 inches high
 - b. 9 inches high
 - * c. 6 inches high
 - d. 3 inches high
- 4.57** **Using the Imperial system of measurement; how far apart are draft mark numbers?**
- a. 12 inches
 - b. 9 inches
 - * c. 6 inches
 - d. 3 inches
- 4.58** **What information is determined from draft readings?**
- a. The depth of the vessel in the water
 - b. The trim and list of the vessel
 - c. The displacement weight of the vessel
 - * d. Answers a., b. and c. are all correct
- 4.59** **When the metric system is used; what size are draft numbers?**
- a. 6 inches high
 - b. 6 centimetres high
 - c. 12 centimetres high
 - * d. 10 centimetres high

- 4.60** **When taking a draft reading which is in metric units; what is the distance between each number?**
- a. 6 inches
 - b. 5 centimetres
 - c. 12 centimetres
 - * d. 10 centimetres
- 4.61** **Which standard covers pre-loading inspection of vessels' tanks?**
- a. EI HM 4
 - b. ISO 3170
 - * c. API MPMS Chapter 17.8
 - d. Answers a., b. and c. are all wrong
- 4.62** **What is a 'wall wash test'?**
- a. A procedure involving high pressure automated washing of the walls of a tank to remove any cargo residue
 - * b. The activity of rinsing the wall of a tank with a solvent and obtaining a sample of the previous product(s) to determine compatibility with the product to be loaded
 - c. A procedure in which a tank is washed with caustic solution to remove surface build-up
 - d. Answers a., b. and c. are all wrong
- 4.63** **What is a 'wipe test'? as per API MPMS Chapter 17.8?**
- a. The procedure of wiping sample containers to ensure they are clean before being submitted to the laboratory
 - * b. The procedure of physically wiping a tanks' interior surface with absorbent white rags to test for possible contamination
 - c. A specialized laboratory test for the presence of water, iron, polymers and emulsion
 - d. Answers a., b. and c. are all wrong

- 4.64** **What should the number of areas in a cargo tank to be wall washed be based upon?**
- a. The last cargo
 - * b. The tank capacity
 - c. The amount of wall wash medium you have
 - d. The age of the vessel
-
- 4.65** **When carrying out a wall wash test of a vessel's cargo tank a number of discoloured areas on the tank surface are noted. If the discoloured areas are less than 20% of the tank's surface area, can these areas be sampled (wall washed) and included the tank sample?**
- * a. Yes
 - b. No
 - c.
 - d.
-
- 4.66** **When carrying out a wall wash test of a vessel's cargo tank a number of discoloured areas, tank coating breaks and exposed sections on the tank surface are noted. If these areas are greater than 20% of the tank's surface area, what action should be taken?**
- a. The areas should be washed and the wall washings included with those from the rest of the tank
 - b. The areas should be noted on the inspection report but should not be washed
 - * c. The areas should be washed and the wall washings from these areas kept in a separate bottle
 - d. The areas can be ignored

- 4.67** **Should a wall wash be performed on a wet tank surface?**
- a. Yes
 - * b. No
 - c.
 - d.
- 4.68** **What must be determined at a pre-loading tank inspection key meeting between vessel's personnel, shore personnel and inspection personnel?**
- a. Tank number, tank capacity, intended cargo volume
 - b. Method of tank cleaning and the last three cargoes
 - c. The contents of adjacent tanks
 - * d. Information a., b. and c. must all be determined
- 4.69** **A 'deck level' inspection is the most effective form of tank inspection.**
- a. True
 - * b. False
 - c.
 - d.
- 4.70** **During a tank entry inspection, which of the following is not correct?**
- * a. Since more than one person will be entering the tank, it is not necessary to have a standby person at the hatch
 - b. All pipelines should be drained and verified empty
 - c. The tank atmosphere should be tested for safe entry
 - d. All surface areas should be checked for possible contamination, tank coating condition and loose rust
- 4.71** **When wall washing a tank, which of the following is correct?**
- a. Tank bottoms (floor) normally do not require wall washing
 - b. There are two wall wash methods, blotter and funnel
 - c. Each wall wash area should be at least 1m x 1m [3 feet by 3 feet]
 - * d. Answers a., b. and c. are all correct

- 4.72** It is not necessary to prepare a blank of the wall wash liquid if it is supplied by a certified Laboratory.
- a. True
 - * b. False
 - c.
 - d.
- 4.73** Pre-loading tank inspection may be limited to gauging OBQ.
- * a. True
 - b. False
 - c.
 - d.
- 4.74** Who is responsible for determining that cargo on a vessel is loaded only into tanks with surfaces or coatings compatible with the cargo?
- a. The independent Inspector
 - b. The shipper of the cargo
 - * c. Vessel's personnel
 - d. Terminal personnel
- 4.75** Which of the following is most likely to require a tank-entry inspection?
- * a. Petrochemicals
 - b. Jet fuel
 - c. Diesel fuel
 - d. Heavy fuel oil
- 4.76** Why should you never break blisters in a tank coating and never disturb piles of debris on a tank floor when performing a tank entry inspection?
- a. The tank atmosphere may be adversely affected
 - b. The Inspector may come into contact with potentially dangerous, unknown material
 - c. It is the responsibility of vessels' personnel to remove debris and prepare the tank surface before the tank is loaded
 - * d. Answers a., b. and c. are all correct

- 4.77** When reading the draft marks on a barge or vessel, which part of the number indicates the actual zero point (start) of the number in question?
- * a. The lower edge of the number
 - b. The upper edge of the number
 - c. The mid point of the number
 - d.
- 4.78** What should a sea valve be sealed to?
- a. The pump-man's wheel wrench
 - b. An adjacent static object such as another valve or railing
 - * c. The main body of the sea valve
 - d. The nameplate on the valve wheel
- 4.79** According to Energy Institute HM28 / HM29 API MPMS Chapter 17.1, what should happen as part of a shore inspection?
- a. The Terminal should tell the Inspector the condition of the line
 - * b. A line fullness verification procedure should be requested to verify line condition
 - c. Unless instructed otherwise, the Inspector should assume that the line is full before and after transfer of product
 - d. Answers a., b. and c. are all correct
- 4.80** If a vessel is discharging under closed gauging conditions and the valve adapters on board are not compatible with the inspector's electronic gauging equipment. What action should be taken?
- a. The principal should be contacted for instructions
 - b. The ship's gauging equipment should be used
 - * c. The ship's gauging equipment should be used but only after it has been verified against inspection company equipment and results recorded
 - d. A manual tape should be used with open gauging

- 4.81** **Independent inspectors are not expected to correct barge tank gauges/dips for trim because most barges do not have trim tables.**
- a. True
 - * b. False
 - c.
 - d.
- 4.82** **What should an inspector do if asked to sign a Dry Certificate:**
- a. Sign it if reasonably sure the tanks are dry
 - b. Sign it if the ship's crew confirms that the tanks are dry
 - * c. Refuse to sign as per TIC Council guidelines
 - d. None of the above
- 4.83** **It is acceptable for an inspector to sign Dry Certificates, Vessel Cleanliness certificates showing that cargo tanks are suitable for the intended cargo, ROB certificates with pumpability statements, and pumping logs.**
- a. True
 - * b. False
 - c.
 - d.
- 4.84** **"The best way to prove the liquid/non liquid nature of ROB/OBQ is to have a sample"**
- * a. True
 - b. False
 - c.
 - d.
- 4.85** **What does API MPMS Chapter 17.9 / EI HM 49 cover:**
- a. Temperature
 - b. Sampling
 - * c. Vessel Experience Factors
 - d. Gauging

- 4.86** Can a compartmental VEF be established for vessels regularly carrying multiple cargoes?
- * a. Yes
 - b. No
 - c.
 - d.
- 4.87** When calculating a VEF which of the following data would be listed on the sequential log but non-qualifying?
- a. Vessel to vessel transfers with only vessel measurements
 - b. First voyage following dry dock when no modifications made
 - c. Change to Gross error
 - * d. Answers a. and c. are correct
- 4.88** When calculating a VEF, only the most recent twenty voyages should be used:
- * a. True
 - b. False
 - c.
 - d.
- 4.89** A VEF should be based upon at least five qualifying voyages:
- * a. True
 - b. False
 - c.
 - d.
- 4.90** According to API 17.9 / HM 49, Which entity determines the voyage number
- a. The client / principal
 - * b. The vessel
 - c. The inspection company
 - d. The port authority

- 4.91** **If the primary method in API 17.9/HM 49 does not produce a VEF what actions should be taken**
- a. Nothing, as a VEF cannot be calculated
 - * b. Use the alternate method, if agreed by all commercial parties
 - c. Use a previous edition of the VEF standard
 - d. None of these choices are correct
-
- 4.92** **Where visual tank inspection is permitted and possible, what should the inspector record?**
- a. The condition of tanks (coating and corrosion)
 - b. An estimate of the presence of any residues
 - c. Details of the previous cargoes
 - * d. Answers a., b. and c. are all correct
-
- 4.93** **Where visual tank inspection is not possible, what should the inspector record?**
- a. The condition of tanks
 - * b. An estimate of the presence of any residues by sounding from access points
 - c. Possible sources of contamination
 - d. Answers a. and b. are correct

SECTION 5 - SAFETY

5.01 What should be the first source of information when preparing to sample a new product?

- a. The International Safety Guide for Oil Tankers and Terminals (ISGOTT)
- b. The Petroleum Handbook
- * c. The Safety Data Sheet (SDS) for that product
- d. Energy Institute HM6 / ISO 3170 / ISO 3171 / API Chapter 8

5.02 Regardless of the product, and in accordance with IP475/ISO 3170, what is the absolute maximum level to which sample containers must be filled?

- a. 50%
- b. 80%
- * c. 95%
- d. 100%

5.03 What is the minimum personal protective equipment required when sampling?

- a. Gloves, respirator, hard hat and SCBA
- * b. Gloves, eye protection, hard-hat, gas monitor, flame retardant uniform & safety shoes
- c. Gloves, face-shield, gas monitor and sun glasses
- d. Gloves, uniform, gas monitor and SCBA

5.04 When gauging a tank that is emitting vapours, where should you position yourself?

- a. It is not important
- b. Up-wind of the gauge hatch
- c. With the wind in your face
- * d. With the wind at your left or right side

- 5.05** **When lifting anything heavy, which muscles should take most of the weight?**
- a. Upper arm muscles
 - * b. Leg muscles
 - c. Back muscles
 - d. Answers a., b. and c. are all correct, to distribute the load equally
- 5.06** **When are inspectors permitted to operate valves on board vessels?**
- a. When accompanied by an authorised person on board
 - b. When no-one else is around to do it
 - c. When the vessel staff are too busy to do it themselves
 - * d. Inspectors must not operate vessel valves
- 5.07** **Which of the following safety equipment is not required on every job?**
- a. H₂S monitor
 - * b. SCBA
 - c. Hard hat, safety footwear, gloves
 - d. Long-sleeve, fire resistant clothing
- 5.08** **What should be the first reaction to any injury accident?**
- * a. Raise the alarm to call for help
 - b. To protect the injured person, if possible without risk to yourself, from exposure to further injury
 - c. To render First Aid
 - d. To report immediately to the person's supervisor

- 5.09 The responsibility for an inspector complying with the safety regulations in any terminal belongs to?**
- a. The terminal staff
 - b. The terminal's safety officer
 - * c. The inspector
 - d. The inspector's manager
- 5.10 Portable electronic measurement equipment must be _____ immediately before gauging?**
- a. Checked
 - b. Cleaned
 - c. Calibrated
 - * d. Earthed (grounded)
- 5.11 All samples which are transported between terminals and laboratories or other installations should be labelled in accordance with the globally harmonised system for classification and labelling of chemicals (GHS).**
- * a. True
 - b. False
 - c.
 - d.
- 5.12 What information must GHS sample labels contain?**
- a. Hazard pictograms, signal words and hazard statements
 - b. Product name and precautionary statements
 - c. Information in both a. and b. above
 - * d. Information in a. and b. above and supplier information, including a telephone number
- 5.13 The GHS applies to:**
- a. sample labels only
 - b. Safety Data Sheets (SDSs) only
 - * c. sample labels and SDSs
 - d. specialised chemicals only

- 5.14** Which of the following is defined as a corrosive liquid?
- a. An acid solution
 - b. A caustic solution
 - c. Acid and caustic solutions are not corrosive
 - * d. Acid and caustic solutions are both corrosive
- 5.15** Corrosive liquids will directly injure the body tissue on contact.
- * a. True
 - b. False
 - c.
 - d.
- 5.16** A chemical has a strong odour. What does this indicate?
- a. That a hazard exists
 - b. That the vapour concentration is low
 - c. That the vapour concentration is high
 - * d. Odour is an unreliable source of specific information regarding a chemical
- 5.17** One of the most important features of a hard hat is the distance between the shell and the wearer's head.
- * a. True
 - b. False
 - c.
 - d.
- 5.18** What does H₂S stand for?
- a. Water
 - b. Hydrogen
 - * c. Hydrogen sulfide
 - d. Dihydrosodium
- 5.19** To find out if a material is hazardous, you must consult the SDS.
- * a. True
 - b. False
 - c.
 - d.

- 5.20 Before gauging a tank, how can static electricity be discharged from your body?**
- a. By using a tank gauge meter
 - * b. By touching a grounded structure such as a tank railing, with bare hands
 - c. By using natural fiber sampling cords
 - d. By touching a grounded structure such as a tank railing, while wearing rubber gloves
- 5.21 When using a metal tape to gauge a tank, the tape should always stay in contact with the gauge hatch.**
- * a. True
 - b. False
 - c.
 - d.
- 5.22 While sampling a crude ship, the fire alarm sounds. What action should be taken?**
- a. Grab a type C fire extinguisher and assist the crew
 - b. Close the hatch and call for the launch
 - c. Continue sampling because the crew will take care of the fire
 - * d. Immediately secure your area and report to the muster point
- 5.23 As you enter a bunded/fire wall area to sample a fuel oil tank, you begin to feel dizzy. What action should you take?**
- * a. Get out of the tank area immediately
 - b. Take a deep breath and run for the tank ladder
 - c. Lie down because there is more oxygen closer to the ground
 - d. Immediately put on your respirator with organic cartridges

- 5.24** **How can the opportunity for a build-up and/or discharge of static electricity be reduced?**
- a. By wearing rubber gloves
 - b. By not allowing your hands to slide on the hand rail
 - * c. By grounding yourself and your equipment before opening the gauge/sample hatch and during subsequent operations
 - d. By using stainless steel equipment
- 5.25** **A portable electronic thermometer should always be grounded after the probe has been lowered into the liquid.**
- a. True
 - * b. False
 - c.
 - d.
- 5.26** **What can help prevent a build-up and/or discharge of static electricity when sampling?**
- a. Use of a sampling cord made of synthetic fibre
 - b. Tying the end of the sampling cord to the railing of the tank
 - * c. Use of a sampling cord that contains no synthetic fibre
 - d. Holding the sample cord against the gauge hatch throughout the sampling operation
- 5.27** **Why is it important to wear gloves while sampling?**
- a. So that the sample is not contaminated
 - b. To prevent your hands becoming dirty
 - * c. To prevent hazardous substances being absorbed through the skin
 - d. None of the above are correct

- 5.28** **What should you do to avoid the build-up and/or discharge of static electricity when using a portable electronic thermometer (PET)?**
- a. Hold on to the railing or other metal part of the tank while using the PET
 - * b. Attach the ground wire of the PET to the tank before opening the gauge hatch then slowly lower the probe assembly into the oil
 - c. Since the probe is plastic and does not conduct electricity, no static electricity can form
 - d. Either a., b. or c. is acceptable
- 5.29** **What is the main component of inert gas used on crude oil vessels?**
- a. Carbon sulfide
 - * b. Carbon dioxide
 - c. Oxygen
 - d. Hydrogen
- 5.30** **What is the main component of inert gas normally used on special chemical vessels?**
- * a. Nitrogen
 - b. Carbon dioxide
 - c. Carbon monoxide
 - d. Hydrogen
- 5.31** **Why should pumping be suspended when first-in or first-foot samples are taken?**
- a. To allow any gas to dissipate
 - * b. To allow static electricity to dissipate
 - c. So the vapours don't blow in your face
 - d. To give time for analysis results
- 5.32** **Shipping declaration forms are required whenever a hazardous material is transported on a public road or highway.**
- * a. True
 - b. False
 - c.
 - d.

- 5.33** **What must you do in order to transport flammable liquid samples on a public highway?**
- a. Fully label all samples
 - b. Place the samples in approved DOT containers
 - c. Consult a Safety Data Sheet for the product being transported
 - * d. Answers a., b. and c. are all correct
- 5.34** **What is the correct source of information about the hazards of any product being inspected?**
- a. The inspector's supervisor
 - b. A knowledgeable chemist
 - c. The inspector's previous experience
 - * d. Safety Data Sheets
- 5.35** **What is the most informative source of information about the hazards of a product or chemical?**
- a. The job sheet
 - b. The Bill of Lading
 - * c. The Safety Data Sheet
 - d. The operations supervisor
- 5.36** **Who can supply an SDS?**
- a. The manufacturer of the material
 - b. The seller of the material
 - c. The distributor of the material
 - * d. Answers a., b. and c. are all correct
- 5.37** **A SDS will list what type of protective equipment is required when working with a particular material.**
- * a. True
 - b. False
 - c.
 - d.

- 5.38 When does a confined space exist on a tank with an external floating roof?**
- * a. It is always a confined space
 - b. Only when the tank is empty
 - c. Only when the roof is resting on its legs
 - d. Answers a., b. and c. are all wrong
- 5.39 Which of the following are considered to be confined spaces?**
- a. A cofferdam
 - b. An external floating roof tank
 - c. A ship's pump-room
 - * d. Answers a., b. and c. are all correct
- 5.40 What is the minimum oxygen content for confined space entry?**
- a. 18.6%
 - b. 19.0%
 - * c. 19.5%
 - d. Answers a., b. and c. are all wrong
- 5.41 Products have defined limits of combustion. What are these?**
- a. The Permissible Exposure Limit and the Threshold Limit Value
 - * b. The Lower Explosive Limit, Upper Explosive Limit and the Flash Point
 - c. The Flash Point and the Threshold Limit Value
 - d. The Permissible Exposure Limit and the Lower Explosive Limit
- 5.42 What defines a confined space?**
- a. It has limited means of access and exit
 - b. It is not designed for continuous occupation
 - c. It has limited natural ventilation
 - * d. Answers a., b. and c. are all correct

- 5.43** **Before entering a confined space, which tests are required?**
- a. Oxygen content
 - b. Lower explosive limit
 - c. Toxic vapour testing
 - * d. Answers a., b. and c. are all correct
- 5.44** **According to the 'International Safety Guide for Oil Tankers and Terminals' (ISGOTT), for a tank to be safe for entry, what should the reading on a combustible gas detector be?**
- a. Less than 15% LEL
 - b. Less than 10% LEL
 - * c. Less than 1% LEL
 - d. Less than 0.5% LEL
- 5.45** **Which of the following are examples of a confined space?**
- a. A cargo tank
 - b. A grain silo
 - c. A pump-room on a ship
 - * d. Answers a., b. and c. are all correct
- 5.46** **Someone must always stand watch at the entrance to the confined space while you are in it.**
- * a. True
 - b. False
 - c.
 - d.
- 5.47** **What do the initials 'LEL' stand for?**
- a. Low explosion location
 - b. Low environmental levels
 - c. Lower environmental level
 - * d. Lower explosive limit

- 5.48** **If the atmosphere in a cargo tank is stated to be 'below the LEL' what does this mean?**
- a. There is not enough oxygen in the tank to support combustion
 - b. There is too much hydrocarbon vapor in the tank to support combustion
 - c. Answers a. and b. are correct
 - * d. There is not enough hydrocarbon vapor in the tank to permit combustion.
- 5.49** **What do the initials 'UEL' stand for?**
- a. Upper environmental level
 - b. Unknown environmental level
 - * c. Upper explosive limit
 - d. Unknown explosive levels
- 5.50** **What does an explosimeter (explosion meter) measure?**
- a. The amount of oxygen in a space
 - b. Whether a space is safe for entry
 - * c. Whether or not there is an explosive atmosphere in a space
 - d. The flash point of a gas mixture.
- 5.51** **An explosimeter (explosion meter) measuring LEL% is utilized to sample the atmosphere within a cargo tank and a reading of 15% is observed. What does the reading mean?**
- a. The atmosphere in the tank contains 15% oxygen
 - * b. The atmosphere in the tank is 15% of the lowest concentration of an explosive mixture of air and hydrocarbon vapours
 - c. The atmosphere in the tank is 15% hydrocarbon vapours
 - d. The atmosphere in the tank is a 15% mixture of air and hydrocarbon vapours

- 5.52** **What does an oxygen meter measure?**
- a. The percentage of oxygen below the LEL of a hydrocarbon/air mixture
 - b. The amount of oxygen needed to make a confined space safe for entry
 - * c. The percentage of oxygen contained in the atmosphere being sampled
 - d. Answers a., b. and c. are all wrong
- 5.53** **What is the normal oxygen content of the air?**
- a. 15.1%
 - b. 19.1%
 - * c. 20.9%
 - d. 25.9%
- 5.54** **Which of the following conditions can cause false readings on an explosion meter?**
- a. Low hydrocarbon vapor content
 - b. High moisture content
 - c. Low oxygen content
 - * d. Both b. and c. are correct
- 5.55** **What is the current exposure limit for benzene (8 hour time weighted average)?**
- a. 10 ppm
 - b. 3 ppm
 - c. 5 ppm
 - * d. 1 ppm
- 5.56** **Benzene is a health hazard. Which of the following are likely to contain benzene?**
- a. Crude Oil
 - b. Gasoline
 - c. Pygas
 - * d. Answers a., b. and c. are all correct

- 5.57 The appearance and characteristic odor of benzene is?**
- * a. Clear colorless liquid with a sweet odor
 - b. Clear colorless liquid with a sour odor
 - c. Light brown liquid with no distinguishable odor
 - d. Light brown liquid with a strong pungent odor
- 5.58 How can benzene enter your body?**
- a. By inhalation
 - b. By absorption through the skin
 - c. By ingestion
 - * d. Answers a., b. and c. are all correct
- 5.59 What is the minimum required respirator for working in a benzene environment that is greater than the permitted exposure limit?**
- a. Self contained breathing apparatus
 - b. Full face respirator with an organic vapor cartridge
 - * c. Half-mask respirator with an organic vapor cartridge
 - d. Half-mask respirator with an acid gas cartridge
- 5.60 When working with benzene, in addition to a respirator, hard hat and safety footwear, what other personal protective equipment should be worn?**
- a. Safety glasses and leather gloves
 - b. Leather gloves, long-sleeve coveralls and goggles
 - * c. Rubber gloves, chemical protective clothing, goggles and face shield
 - d. Rubber gloves, goggles, and coveralls
- 5.61 Which of the following statements are correct, when working with benzene?**
- a. A full face or half mask cartridge respirator must be worn for closed or restricted system gauging and sampling
 - b. A self contained breathing apparatus must be used in all open tank situations
 - c. A self contained breathing apparatus must be used if the exposure is expected to exceed 50ppm
 - * d. Answers a., b. and c. are all correct

- 5.62** Can gasoline contain benzene?
- * a. Yes
 - b. No
 - c.
 - d.
- 5.63** Workers who are regularly exposed to benzene should have a regular medical examination.
- * a. True
 - b. False
 - c.
 - d.
- 5.64** What is the permissible exposure limit for benzene (8 hour time weighted average)?
- a. 10 ppm
 - b. 3 ppm
 - c. 5 ppm
 - * d. 1 ppm
- 5.65** What is the appearance and characteristic odour of benzene?
- * a. Clear colourless liquid with a sweet odour
 - b. Clear colourless liquid with a sour odour
 - c. Light brown liquid with no distinguishable odour
 - d. Light brown liquid with a strong pungent odour
- 5.66** What effects may result from chronic exposure (long term) to benzene?
- a. Loss of vision
 - * b. Various blood disorders ranging from anemia to leukemia
 - c. Impaired Disability Syndrome (IDS)
 - d. Answers a., b. and c. are all correct
- 5.67** How heavy are benzene vapours?
- a. Lighter than air
 - * b. Heavier than air
 - c. Same as air
 - d. Answers a., b. and c. are all wrong

5.68 Hydrogen sulfide may be present in many petroleum products and crude oil

- * a. True
- b. False
- c.
- d.

5.69 What are the effects of acute exposure (short term) to benzene?

- a. Shortness of breath, irritability, headache, nausea, dizziness, intoxication
- b. Irritation of the eyes, nose, and respiratory tract
- c. Convulsions and loss of consciousness
- * d. Answers a., b. and c. are all correct

5.70 Who or what should you consult if you need to know detailed safety or exposure information about benzene?

- a. Your doctor or pharmacist
- b. Your Safety Manual
- * c. The Safety Data Sheet
- d. The International Safety Guide for Oil Tankers and Terminals (ISGOTT)

5.71 What is the most immediate hazard of many crude oils?

- a. Benzene
- b. Toluene
- c. Xylene
- * d. Hydrogen sulfide

- 5.72** When working in an environment suspected of containing H₂S, personal monitors must provide an alarm at what limit?
- a. 100 ppm in the USA; 50 ppm or lower in other locations
 - b. 50 ppm in the USA; 20 ppm or lower in other locations
 - * c. 10 ppm in the USA; 5 ppm or lower in other locations
 - d. 0.5 ppm in the USA; 0.2 ppm or lower in other locations
- 5.73** Organic filter respirators are sufficiently effective in a hydrogen sulphide atmosphere to be used for escape purposes.
- a. True
 - * b. False
 - c.
 - d.
- 5.74** Hydrogen sulfide is probably the most dangerous gas commonly encountered in the petroleum industry.
- * a. True
 - b. False
 - c.
 - d.
- 5.75** What are the characteristics of hydrogen sulfide?
- a. It is a pale yellow gas with a sweetish taste and strong pungent odour
 - b. It is a pale yellow gas with the odour of rotten eggs
 - * c. It is a colourless gas with a sweetish taste and the odour of rotten eggs
 - d. It is a colourless gas with little or no odour
- 5.76** What is the time used for TWA (time weighted average) exposure levels?
- a. 4 hours
 - * b. 8 hours
 - c. 12 hours
 - d. 24 hours

- 5.77 Which of the following exposure limits for H₂S (for use with respirators) are correct?**
- a. 500 ppm maximum exposure when using a full face respirator
 - b. 100 ppm maximum exposure when using a half-mask respirator
 - c. A self contained breathing apparatus must be used if the exposure exceeds 500 ppm
 - * d. Only a self contained breathing apparatus is permissible for any exposure above the permissible exposure limit
- 5.78 Refineries are not the only sources of industrial hydrogen sulfide (H₂S). Which of the following are other sources?**
- a. Pulp Mills
 - b. Any agricultural facility where decay of organic matter may occur
 - c. Drilling Rigs
 - * d. Answers a., b. and c. are all correct
- 5.79 What is the maximum permissible 8 hour TWA (time weighted average) exposure level of H₂S?**
- * a. 10 ppm in the USA; 5 ppm or lower in other locations
 - b. 100 ppm in the USA; 50 ppm or lower in other locations
 - c. 20 ppm in all locations
 - d. 50 ppm in the USA; 20 ppm or lower in other locations
- 5.80 What is the short term exposure limit (STEL) for hydrogen sulfide?**
- a. 100 ppm in USA; 50 ppm or lower in other locations
 - b. 50 ppm in USA; 20 ppm or lower in other locations
 - * c. 20 ppm in USA; 10 ppm or lower in other locations
 - d. 2 ppm in USA; 1 ppm or lower in other locations

- 5.81** **Why is the sense of smell not reliable for detecting hydrogen sulfide?**
- a. It is difficult to detect by sense of smell
 - b. The level at which you can smell it is above the permissible exposure limit
 - * c. At 100 ppm a person's sense of smell is deadened within minutes, thereby giving that person a false sense of security
 - d. You might have a cold and be unable to breathe through your nose
-
- 5.82** **When working in hydrocarbon environments you must always wear a H₂S monitor.**
- * a. True
 - b. False
 - c.
 - d.
-
- 5.83** **What is the principal limitation of a filter or cartridge respirator?**
- * a. It does not supply oxygen
 - b. The face piece tends to fog up
 - c. The expense to replace the cartridges
 - d. Keeping the face piece from sweating up
-
- 5.84** **Ladders, planks, and scaffold boards should not be used as walkways (i.e. when boarding vessels, moving between barges, etc.)**
- * a. True
 - b. False
 - c. Only when in exposed seaway conditions
 - d. Only when no gangways are available

- 5.85** **May an inspector board a vessel by means of using a “Pilot’s” ladder?**
- * a. Yes
 - b. No
 - c.
 - d.
- 5.86** **The Short Term Exposure Limit (STEL) defines exposure to a substance over how long?**
- a. 30 minutes
 - b. 60 minutes
 - * c. 15 minutes
 - d. 20 minutes
- 5.87** **When should an inspector access a floating roof?**
- a. Only if to draw samples and no measurement
 - * b. Never unless there is a documented PTW in place with all safety measures in place including a verified means of escape in an incident
 - c. Only if the roof is less than one course of plates (1m [3 feet]) below the top rim
 - d. Only if accompanied by a terminal representative
- 5.88** **High levels of H₂S may be associated with bitumen cargoes**
- * a. True
 - b. False
 - c.
 - d.

- 5.89** **When gauging and sampling on unmanned barges, it is recommended for inspectors not to work unaccompanied**
- * a. True
 b. False
 c.
 d.
- 5.90** **What action should an inspector take if he is not under safety supervision when working in a shore facility?**
- * a. Continue working but report to the office later
 b. Refuse to proceed and use a stop work authority
 c. Continue working as normal but report to the master/site office later
 d. Issue a letter of protest to the vessel or terminal
- 5.91** **What should an inspector do if the task or the working conditions appear to involve risks which are unacceptable or not suitably controlled ?**
- * a. Use the stop work authority until the risks are mitigated
 b. Continue carefully but advise the principal immediately after completion of the task
 c. Always refuse to perform the task
 d. Perform the task only if their supervisor instructs them to

SECTION 6 - SAMPLING

6.01 Which industry documents describe the procedures for manual sampling of petroleum and petroleum products?

- a. API MPMS Chapter 17.1 / EI HM28
- * b. API MPMS Chapter 8.1 / IP 475 / ISO 3170
- c. API MPMS Chapter 8.2 / EI HM6 / ISO 3171
- d. API MPMS Chapter 17.2

6.02 Which of the following types of containers should never be used for handling or storage of jet fuel samples?

- a. Clear glass bottles
- b. Amber glass bottles
- * c. Plastic bottles
- d. Epoxy lined metal cans

6.03 Which of the following types of sample container should be used to obtain an initial first foot sample?

- * a. Clear glass bottles
- b. Amber glass bottles
- c. Plastic bottles
- d. Epoxy lined metal cans

6.04 Which of the following products would normally be stored in amber bottles?

- * a. Gasoline
- b. Fuel oil
- c. Heavy aromatics
- d. Vacuum Gas Oil

6.05 According to API MPMS Chapter 8.1, which of the following types of container closure devices should not be used with glass bottles?

- a. Plastic screw caps
- * b. Rubber stoppers
- c. Metal screw caps
- d. Cork stoppers

- 6.06 Which product requires particular care when selecting a sample container?**
- a. Gasoline
 - b. Fuel oil
 - c. Benzene
 - * d. Jet fuel
- 6.07 Which documents contain guidance for selecting sample containers?**
- a. API MPMS Chapter 8.1 / ISO 3170
 - b. API MPMS Chapter 8.2 / IP 476 / ISO 3171
 - * c. API MPMS Chapter 8.3 / EI HM 92
 - d. API MPMS Chapter 8.4
- 6.08 For which products is it recommended to rinse the container with the liquid to be sampled before drawing the sample?**
- a. Jet fuel samples
 - b. Petrochemical samples
 - c. Vapour pressure samples
 - * d. Answers a., b. and c. are all correct
- 6.09 Jet fuel should not be sampled with equipment that contains brass, copper or copper alloy.**
- * a. True
 - b. False
 - c.
 - d.
- 6.10 What equipment is preferred to lower a sample bottle to the required level?**
- a. Ullage tape
 - * b. Natural fibre cord or non-sparking chain marked to indicate when the correct level has been reached
 - c. Innage tape
 - d. Brass sampling cage

- 6.11 Which equipment is best for sampling free water in a crude oil tank?**
- a. Zone sampler
 - * b. Dead bottom sampler
 - c. Bottle and sample cage
 - d. Weighted bottle and cord
- 6.12 What type of equipment would you use to sample liquid in a 55-gallon drum?**
- a. A dead-bottom sampler
 - b. A bottle and cage.
 - * c. A sampling tube.
 - d. A dipper sampler.
- 6.13 Which of the following samples could be taken with a zone sampler?**
- a. U, M, L samples
 - b. Running samples
 - c. Spot samples
 - * d. Answers a., and c. are correct
- 6.14 When sampling volatile liquids, why is it generally better to use a sampling cage and bottle and not a weighted sampling can/beaker?**
- a. The equipment is easier to handle
 - b. A can sample is probably less representative
 - * c. Loss of light ends is likely when the sample is transferred from the can/beaker
 - d. Sample bottles are readily available
- 6.15 When should a free water sample be taken ?**
- a. When requested by the customer.
 - b. They are not necessary.
 - c. Immediately after every loading, except for chemicals.
 - * d. Whenever there is a sufficient quantity to sample

- 6.16** **Why is drawing free water samples important?**
- a. To check for contaminated water under gasoline
 - * b. To determine the likely source of the free water
 - c. To determining the influence of free water on the API gravity of a crude oil cargo
 - d. Answers a., b. and c. are all wrong
- 6.17** **A representative sample is a portion extracted from the total volume that contains its constituents in the same proportions as those present in the total volume.**
- * a. True
 - b. False
 - c.
 - d.
- 6.18** **Why do sampling standards recommend that a vapour space should be left at the top of each sample container?**
- a. To permit the surface of the liquid to be visible in the laboratory
 - b. To allow space to test the vapour content of the sample
 - * c. To allow space for safe expansion of the liquid
 - d. To avoid the loss of light components
- 6.19** **What is the name of a sample obtained by lowering a stoppered container to the outlet suction level of a tank, removing the stopper and withdrawing the container at a steady rate?**
- a. Spot sample
 - b. Running sample
 - * c. All-levels sample
 - d. Composite sample

- 6.20** What is the name of a sample obtained by lowering an unstoppered container to the outlet suction level of a tank and withdrawing the container without stopping?
- a. Multi-level sample
 - * b. Running sample
 - c. All-levels sample
 - d. Composite sample
- 6.21** Before sampling oil in a tank, it is necessary to locate the oil/water interface.
- * a. True
 - b. False
 - c.
 - d.
- 6.22** Before sampling a clean product or petrochemical, the container should always be rinsed with the product when possible.
- * a. True
 - b. False
 - c.
 - d.
- 6.23** Sample containers may be 100% full when the vapour pressure of the product sampled is less than 10 psi.
- a. True
 - * b. False
 - c.
 - d.
- 6.24** After taking a spot sample of gasoline, it is permissible to immediately pour off some of the product to allow room in the container for expansion.
- * a. True
 - b. False
 - c.
 - d.

6.25 How is an all-levels sample obtained?

- a. By lowering the unstoppered device to the bottom of the outlet suction level, but always above any free water, and raising it at a uniform rate such that it is between 70% and 85% full when withdrawn from the product.
- b. By blending tank upper, middle and lower samples.
- * c. By lowering the stoppered device to the bottom of the outlet suction level, but always above any free water, then opening the sampler and raising it at a uniform rate such that it is between 70% and 85% full when withdrawn from the product.
- d. By lowering a stoppered device to the bottom of the product in a tank, then opening the sampler and raising it at a uniform rate until the container is full.

6.26 How is a running sample obtained?

- * a. By lowering an open (un-stoppered) sampling device to the bottom of the outlet suction level, but always above any free water, and returning it to the top of the product at a uniform rate such that the sampling device is between 70% and 85% full when withdrawn from the product.
- b. By lowering a stoppered sampling device to the level of the outlet, then opening the sampler and raising it at a uniform rate such that the sampling device is between 70% and 85% full when withdrawn from the product.
- c. By lowering a stoppered sampling device to the bottom of the tank contents, then opening the sampler and raising it at a uniform rate until it is full.
- d. By lowering an unstoppered sampling device to the bottom of the tank contents, and then raising it at a uniform rate until it is full.

- 6.27** When sampling heavy fuel oil, crude oil or petroleum products in a tank with non-liquid or sediment deposits on the bottom, why may samples not be representative?
- a. Because the material may be non-homogeneous
 - b. Because the concentration of entrained water is higher near the bottom
 - c. Because the interface between the oil and water is difficult to measure accurately
 - * d. Answers a., b. and c. are all correct
- 6.28** During a marine custody transfer, which of the following is the preferred sample to best represent the cargo transferred?
- a. A composite of shore tank samples.
 - b. A shore tank sample after a transfer
 - * c. Automatic pipeline samples obtained throughout the transfer
 - d. Vessel composite samples
- 6.29** After obtaining a tank running sample, the inspector notices that the sampling bottle is full on withdrawing it from the tank. What should the inspector do?
- a. Pour some of the sample into a second container
 - b. Pour some of the sample out of the bottle
 - * c. Retake the sample to comply with the method
 - d. Answers a., b. or c. are all correct
- 6.30** A storage tank is manually gauged and found to contain 4.0 metres [12 feet] of product. How many spot samples as a minimum should be obtained from this tank?
- * a. 2 (Upper and lower)
 - b. 3 (Upper, middle and lower)
 - c. 1 (Middle)
 - d. None

- 6.31 Why should sampling cord not be allowed to fall on the deck or tank roof?**
- a. It could become contaminated
 - b. It could make a mess that could cause a potential slipping hazard
 - c. The cord could become damaged
 - * d. Answers a. and b. are correct
- 6.32 For a running sample to be taken correctly, the sample container must be?**
- a. At least half full
 - b. A zone sampler
 - c. A bottle and cage
 - * d. Between 70% to 85% full
- 6.33 Which of the following statements is correct?**
- a. Closed and restricted sampling equipment is essentially the same
 - b. Restricted sampling equipment may allow small amounts of vapour to escape to atmosphere
 - c. Closed sampling equipment is designed to prevent any escape of vapour to atmosphere
 - * d. Answers b. and c. are correct
- 6.34 When sampling a shore tank containing a product with an observed density of 1100 kg/m³ [API -2°] and the main concern is water, where would the water probably be found?**
- a. 15 cm [6"] off the bottom
 - b. Stratified between the lower and middle levels
 - * c. Floating on top of the cargo
 - d. No water can be found in oils with a density greater than 1000 kg/m³[with negative API]

- 6.35** **Why is a running sample not acceptable if the container is brought up full?**
- * a. There is no way to tell when the bottle filled up
 - b. There would be too much oil to test the density
 - c. There is a chance of contamination from the bottle cap
 - d. As the bottle warms up, it could shatter
- 6.36** **What laboratory test will most likely be affected by not using dedicated sampling equipment for individual products or product groups?**
- a. colour
 - b. flashpoint
 - c. sulphur
 - * d. Answers a., b. and c. are all correct
- 6.37** **Since the volume of material in the tank does not affect laboratory analysis, tanks that are sampled do not need to be gauged.**
- a. True
 - * b. False
 - c.
 - d.
- 6.38** **When taking a first foot sample of a jet fuel cargo it is recommended to**
- * a. Use a clear bottle
 - b. Use only steel sampling cans
 - c. Use only a clean zone sampler
 - d. Use an amber bottle

- 6.39** **What is the principal reason for taking dead-bottom samples.**
- a. To determine if sediment is present
 - b. To obtain a sample for sulfur & viscosity determination
 - * c. To locate any free water not identified by water paste and sediment
 - d. Bottom samples need not be taken if water paste indicates that no water is present
- 6.40** **If the sample bottle comes up full when taking a running sample what action should be taken?**
- a. Pour out 20% - 25% of the sample, then cap and label the sample
 - b. Cap and label sample then place it in an ice chest
 - c. Make a special notation on the sampling report
 - * d. Discard the sample and re-sample the tank so that the bottle is no more than 85% full
- 6.41** **When taking a running sample of a clear product such as jet fuel or a water-white chemical what procedure should you follow?**
- a. Rinse the inside of the sample bottle with product prior to taking the sample
 - b. Take a sample in a clear bottle to visually check the colour
 - c. Ensure that product running down the sample cord cannot contaminate the sample
 - * d. Answers a., b. and c. are all correct
- 6.42** **Samples should not be taken from an unslotted or unperforated standpipe.**
- * a. True
 - b. False
 - c.
 - d.

- 6.43** **A sample can or bottle should never be capped if it is more than 95% full.**
- * a. True
 - b. False
 - c.
 - d.
- 6.44** **When taking liquid samples for hydrogen sulphide testing in accordance with IP 570 [ASTM D7621] what is the maximum level to which sample containers must be filled?**
- a. 50%
 - b. 80%
 - * c. 95%
 - d. 100%
- 6.45** **Before taking a line sample it is important to?**
- a. Ground your equipment
 - * b. Flush the tap and sample line until they are completely purged
 - c. Call your supervisor
 - d. Answers a., b. and c. are all correct
- 6.46** **During preliminary sampling of a shore tank that will be used to load a vessel, you should also obtain a liquid level measurement**
- * a. True
 - b. False
 - c.
 - d.

- 6.47** **Where may volumetric composite samples be prepared?**
- a. Only in a laboratory
 - b. On board a vessel if separate samples are taken to the laboratory for analysis
 - * c. Preferably in a laboratory but also at another location if conditions and equipment allow the sample to be composited in proportion to the volume of material in each compartment
 - d. On board a vessel for crude oil cargos only
- 6.48** **At what point is a dead bottom sample taken?**
- a. 15 cm [6 inches] below the outlet
 - b. 10 cm [4 inches] below the outlet
 - * c. At the lowest point in the tank
 - d. Immediately above the free water level
- 6.49** **What is the name for a sample taken at a specific point in a tank?**
- a. An all level sample
 - b. A running sample
 - * c. A spot sample
 - d. A single-tank composite sample
- 6.50** **What is the term for a blend of samples from different shore tanks, mixed proportionally for testing?**
- a. A composite spot sample
 - b. A loading sample
 - c. A clearance sample
 - * d. A multiple tank composite sample

- 6.51 At what level in a product tank is a top sample taken?**
- a. Middle of the upper third of the liquid
 - b. 15 cm [6 inches] above the tank outlet
 - c. Middle of the lower third of the tank
 - * d. 15 cm [6 inches] below the surface of the liquid
- 6.52 A bottom sample may not always be taken at the very bottom of a tank. What is the correct procedure?**
- * a. Always specify the location where the sample was taken, for example 'Approximately 15 cm [6 inches]' from the bottom
 - b. Always take a bottom sample 5 cm [2 inches] off the actual bottom because that is where the neck of the bottle will rest when the bottle is on its side
 - c. Always use a dead bottom sampler to draw bottom samples
 - d. Always use a zone sampler to draw bottom samples
- 6.53 Where is a 'lower' sample taken from?**
- a. The bottom of the tank
 - b. Just above the water level
 - * c. The mid-point of the bottom third of the liquid
 - d. At the level of the tank outlet/inlet pipe
- 6.54 A storage tank was manually gauged and found to have a product innage of 12.000 m [38 feet 6 inches]. The tank gauge height is 13.000 m [48 feet 10 inches]. At what innage level should the lower spot sample be obtained?**
- a. 150 mm [6 inches] from the tank bottom
 - b. At the outlet (suction) level
 - * c. 2.000 m [6 feet 5 inches] from the tank bottom
 - d. 4.000 m [12 feet 10 inches] from the tank bottom

- 6.55** **A storage tank was manually gauged and found to have a product innage of 11.500 m [38 feet 6 inches] . The tank gauge height is 12.500 m [48 feet 10 inches] . At what innage level should the middle product spot sample be obtained?**
- a. 6.750 m [12 feet 10 inches] from the tank bottom
 - * b. 5.750 m [19 feet 3 inches] from the tank bottom
 - c. 6.250 m [24 feet 5 inches] from the tank bottom
 - d. 6.250 m [6 feet 5 inches] below the surface of the product
- 6.56** **A storage tank was manually gauged and found to have a product innage of 9.000 m [38 feet 6 inches]. The tank gauge height is 12.000 m [48 feet 10 inches]. At what innage level should the upper product spot sample be obtained?**
- * a. 7.500 m [32 feet 1 inch] from the tank bottom
 - b. 2.000 m [5 feet 5 inches] below the surface of the product
 - c. 11.850 m [40 feet 9 inches] from the tank bottom
 - d. 150m [6 inches] below the surface of the product
- 6.57** **Where is an 'upper' sample taken from?**
- a. The surface of the liquid
 - b. 150 mm [6 inches] below the surface of the liquid
 - * c. The mid-point of the upper third of the liquid
 - d. Anywhere in the top portion of the tank
- 6.58** **Which of the following statements about upper, middle, and lower samples is correct?**
- a. They can be taken in any order.
 - b. They must be taken in the order lower, middle, upper.
 - * c. They must be taken in the order upper, middle, lower.
 - d. They are less reliable than an all-levels sample, no matter how they are taken

- 6.59** When upper-middle-lower samples are taken from a tank, from what point is the lower sample taken?
- a. 1/3 of the liquid height from the tank bottom
 - b. At the middle of the tank outlet fitting
 - * c. 1/6 of the liquid height from the tank bottom
 - d. 150 mm off the tank bottom
- 6.60** When drawing upper-middle-lower samples from any tank, which sample should be taken first?
- a. Lower
 - b. Middle
 - * c. Upper
 - d. It doesn't matter
- 6.61** When upper-middle-lower samples are taken from a tank, what point is the upper sample taken from?
- a. 1/3 of the liquid height from the tank bottom
 - b. At the middle of the tank outlet fitting
 - * c. At the middle of the upper third of the tank contents
 - d. 15 cm [6 inches] off the tank bottom
- 6.62** When drawing upper-middle-lower samples from any tank, which sample should be taken last?
- * a. Lower
 - b. Middle
 - c. Upper
 - d. It doesn't matter
- 6.63** When drawing upper-middle-lower samples from any tank, which sample should be taken second?
- a. Lower
 - * b. Middle
 - c. Upper
 - d. It doesn't matter

- 6.64** **At what vertical location in the liquid is an upper sample taken?**
- * a. 1/6 of the liquid depth below the surface of the liquid
 - b. 25 mm [1 inch] below the surface of the liquid
 - c. 150 mm [6 inches] below the surface of the liquid
 - d. The middle of the lower third of the tank
- 6.65** **An automatic in-line sampling system will collect free water and entrained water.**
- * a. True
 - b. False
 - c.
 - d.
- 6.66** **Automatic samplers can be either time proportional or flow proportional.**
- * a. True
 - b. False
 - c.
 - d.
- 6.67** **Which of the following items are parts of an automatic sampling system?**
- a. Probe
 - b. Receiver
 - c. Controller
 - * d. Answers a., b. and c. are all correct
- 6.68** **The sample receiver of an automatic sampling system must be inspected to ensure that it is clean and dry before it is used.**
- * a. True
 - b. False
 - c.
 - d.

- 6.69** Before testing, the product in the receiver of an automatic sampler must be mixed to homogenize the sample.
- * a. True
 - b. False
 - c.
 - d.
- 6.70** The controller on an automatic sampler is a device that governs the operation of the sample extractor.
- * a. True
 - b. False
 - c.
 - d.
- 6.71** According to API MPMS Ch 8.2/ASTM D4177, sampling in a time proportional mode is acceptable if the flow rate variation is less than ± 10 percent of the average rate over the entire parcel.
- * a. True
 - b. False
 - c.
 - d.
- 6.72** Both free water and entrained water are found in the sample taken by an automatic in-line sampling system.
- * a. True
 - b. False
 - c.
 - d.
- 6.73** What should be used to take a sample that is to be tested for vapour pressure?
- a. A zone sampler
 - b. A glass bottle with suitable cage or weight
 - c. A dedicated closed or restricted vapour pressure sampler
 - * d. Answers b. and c. are correct

- 6.74** When taking samples for vapour pressure testing, samples must not be composited.
- * a. True
 - b. False
 - c.
 - d.
- 6.75** When drawing a running sample for RVP, how full should the sample bottle be when withdrawn from the tank?
- a. 50%-60% full
 - * b. 70-80% full
 - c. 80-90% full
 - d. 100% full
- 6.76** When/where should samples be labeled?
- a. In the laboratory.
 - * b. Immediately after the sample is obtained.
 - c. Before transportation to the laboratory.
 - d. Immediately upon arrival in the laboratory
- 6.77** Why is it important to label all samples as soon as possible?
- a. National and/or local Government regulations require it.
 - b. An incorrectly labeled sample could generate a legal action
 - c. It is easy to label samples incorrectly if they are not labelled promptly
 - * d. Answers a., b. and c. are all correct
- 6.78** When should a sample be labelled?
- a. On returning to the office
 - b. After removing them from the sample transportation box.
 - c. Just before leaving the facility
 - * d. Immediately after it is obtained

- 6.79** When drawing gasoline/naphtha samples for vapour pressure testing which comment(s) apply to the sample containers?
- a. They should be kept as cool as possible
 - b. They should be filled to approximately 75% level
 - c. They should be fitted with vapour tight lids
 - * d. Answers a., b. and c. are all correct
- 6.80** What is the most important feature of a container to be used for a sample of gasoline/naphtha for vapour pressure testing?
- a. It should be made of glass
 - b. It should be made of plastic
 - c. It should be made of metal
 - * d. It should be fitted with a vapour-tight lid
- 6.81** Why is a 'first foot' sample taken?
- a. To determine the quality of the product in the shore tank
 - b. To confirm that the vessel's tanks are clean
 - c. To confirm that the product in the shore pipeline meets the specification
 - * d. As an indication that the cargo is has not been contaminated by residues from the ship's manifold or lines
- 6.82** According to ISO 3171 and API Chapter 8.2 what is the number of grabs suggested when using an automatic sampler for transfers lasting over 6 hours?
- a. 100,000
 - * b. 10,000
 - c. 1,000
 - d. 100
- 6.83** Sealing of samples that are passed to third parties is not required by the TIC Council Code of Practice.
- a. True
 - * b. False
 - c.
 - d.

- 6.84** **When samples are to be taken jointly with another inspection company the inspector must ensure that:**
- a. Samples are sealed
 - b. Only the most senior inspector signs all the sample labels
 - c. Sample labels bear the marks of both inspection companies together with the other usual information
 - * d. Answers a. and c. are correct
- 6.85** **Samples given to third parties must be:**
- * a. individually labelled, sealed, and records kept of the respective seal numbers
 - b. signed by the third party and sealed in their presence
 - c. given only if the third parties accept full responsibility that the samples are representative
 - d. Answers b. and c. are correct
- 6.86** **Why are amber bottles preferred to clear bottles for long term storage:**
- * a. Amber glass protects sample from exposure to light
 - b. Amber glass is cheaper
 - c. Clear glass is more likely to crack and leak sample
 - d. Answers a, b and c are all correct
- 6.87** **Should the levels of H₂S vapor in a tank headspace be declared or measured to be of 500 ppm or more, no manual sampling takes place with either open or closed equipment to ensure the safety of personnel.**
- * a. True
 - b. False

SECTION 7 - TANK GAUGING

7.01 What is commonly meant by the term 'dip'?

- a. Ullage
- * b. Innage
- c. Free water measurement
- d. Swing gauge

7.02 What occurs when a shore tank is filled to a level in the 'critical zone'?

- a. The flexing bottom of a tank is at its highest point
- b. The tank will overflow if more liquid is added
- c. The floating roof is no longer resting on its legs
- * d. The floating roof is only partially afloat and the capacity table may be inaccurate

7.03 A 'tank capacity table' is also referred to as a 'tank strapping table'.

- * a. True
- b. False
- c.
- d.

7.04 What is a 'master tape'?

- a. The only tape that may be used to take custody transfer measurements
- b. A tape belonging to the National Certification Body
- c. A tape to be used only for tank calibration
- * d. A reference tape, traceable to National Standards to be used only for verifying the accuracy of tapes used in the field

- 7.05 What does an innage/sounding measure?**
- a. The distance from the surface of the liquid in the tank to the reference gauge point of the tank.
 - b. The distance between the point where the floating roof of the tank is floating freely and the point where it is resting fully on it's supports.
 - * c. The level of liquid in a tank measured from the datum plate or tank bottom to the surface of the liquid.
 - d. The distance from the tank datum plate or bottom to the tank reference gauge point.
- 7.06 What does an outage/ullage measure?**
- a. The distance from the tank datum plate or bottom to the tank reference point.
 - * b. The distance from the surface of a liquid in a tank to the reference gauge point of the tank.
 - c. The amount of product transferred out from a tank.
 - d. The level of liquid in a tank measured from the tank bottom to the surface of the liquid.
- 7.07 What is water finding paste used for?**
- a. To determine the S&W of the product in the tank
 - b. To detect the presence of suspended water within the product in the tank
 - * c. To indicate the free water interface within the tank
 - d. Answers a., b. and c. are all wrong
- 7.08 An innage gauge bob is pointed to aid in penetration of tank non-liquid. Where is its zero point?**
- a. Top of the eye
 - b. Bottom of the eye
 - * c. Tip of the bob
 - d. Inside of the tape swivel

7.09 What is the observed gauge height of a tank?

- * a. The distance from the reference gauge point to the bottom of the tank or the datum plate as measured during the gauging operation
- b. The distance from the reference gauge point to the bottom of the tank or the datum plate as shown on the tank capacity tables
- c. The distance from the ullage pipe to the liquid level
- d. Usually written somewhere on the ullage pipe

7.10 What is innage or dip?

- * a. The distance from the datum plate or the tank bottom to the surface of the product
- b. The measurement from the tank bottom to reference point
- c. The cut found on the bob
- d. The distance from the reference point to surface of the product

7.11 What is the distance between the point where the floating roof begins to rest on its normal supports and the point where it begins to float freely known as?

- a. The floating level
- b. The lower leg level
- * c. The critical zone
- d. The displacement level

7.12 On a shore tank, what is the term for the distance between the Reference Gauge Point and the Datum Point, as measured at the time of gauging?

- a. Observed reference point
- b. Reference gauge height
- c. Total gauge height
- * d. Observed reference height

- 7.13 What is a tank datum plate?**
- a. The position on a tank where the gauge height is noted.
 - b. The point marked on the gauge hatch of a tank to indicate the position from which the tank is to be gauged.
 - c. The plate on the tank shell that lists the tank general data such as roof weight, height of tank, etc.
 - * d. A plate placed in the tank and directly under the reference gauge point to provide a fixed contact surface.
- 7.14 When rainwater or snow accumulates on the roof of an external floating roof tank, what will happen to the gauged level in the tank?**
- a. It will decrease
 - b. It will remain the same
 - * c. It will increase
 - d. Answers a., b. and c. are all wrong
- 7.15 An innage (dip) tape and bob may be used to take an outage (ullage) gauge.**
- * a. True
 - b. False
 - c.
 - d.
- 7.16 An ullage gauge is the same thing as an outage gauge.**
- * a. True
 - b. False
 - c.
 - d.
- 7.17 According to API MPMS Chapter 3.1A/EI HM4, when must gauge tapes be verified for accuracy?**
- * a. Before initial use and once per year
 - b. Once per month
 - c. Before each use
 - d. Once every three months

- 7.18** Some measurement systems are gas-tight (closed) and other systems (restricted) permit some vapour to escape around the Portable Measurement Unit (PMU) when tanks are under positive pressure.
- * a. True
b. False
c.
d.
- 7.19** Which gauge measures the distance from the datum plate or tank bottom to the surface of the liquid?
- * a. Innage
b. Ullage
c.
d.
- 7.20** Which gauge measures the distance from the surface of the liquid to the tank reference gauge point?
- * a. Innage or dip
b. Ullage
c.
d.
- 7.21** What is the measured distance from the datum plate or tank bottom to the reference gauge point called?
- * a. The observed reference height
b. The innage gauge height
c. The reference gauge height
d. The ullage gauge height
- 7.22** What is the term for the distance from the datum plate or tank bottom to the reference gauge point, as shown on the tank capacity table?
- * a. Observed gauge height
b. Innage gauge height
c. Reference gauge height
d. Ullage gauge height

- 7.23** When taking a level measurement three gauge tape readings should be within____
- a. 12mm or 1/2 inch
 - b. 6mm or 1/4 inch
 - * c. 3mm or 1/8 inch
 - d. 9mm or 1/3 inch
- 7.24** Which of the following can affect the accuracy of tank's capacity table?
- a. The flexing of the tank bottom with the transfer of contents
 - b. Expansion at the vertical middle (barreling) occurring during filling
 - c. Accumulated deposits of previous contents on the tank shell
 - * d. Answers a., b. and c. are all correct
- 7.25** If a portable measurement unit (PMU) is used, which of the following procedures should be followed to measure free water on a vessel before discharge?
- a. Rely on the PMU alone for free water level measurement
 - b. Use water-finding paste with a sounding rod/rule or dip tape
 - * c. Answers a. and b. are both correct
 - d. Recommend to the terminal that the free water received and measured ashore be applied to the vessel figures

- 7.26 To determine the ullage of the liquid in a tank using an innage tape and bob assembly, what procedure should be followed?**
- * a. Read the immersion depth of the tape at the reference gauge point and subtract the oil cut reading on the bob
 - b. Read the immersion depth of the tape at the reference gauge point and add the oil cut reading on the bob
 - c. Subtract the oil cut on the bob from the tank reference gauge height indicated on the tank capacity table
 - d. Subtract the oil cut on the bob from the measured tank reference gauge height
- 7.27 Which industry documents describe the procedures for the gauging of petroleum or petroleum products?**
- a. API MPMS Chapter 17.1/EI HM28
 - b. API MPMS Chapter 17.9/EI HM49
 - * c. API MPMS Chapter 3/EI HM4
 - d. API MPMS Chapter 1/EI HM0
- 7.28 When gauging light products, it is permissible to use chalk or talcum powder to facilitate reading the cut on the tape.**
- a. True
 - * b. False
 - c.
 - d.
- 7.29 When using water finding paste in light products, how long should the gauging bar be left in position?**
- a. A minimum of 5 seconds
 - * b. A minimum of 10 seconds
 - c. A minimum of 30 seconds
 - d. A minimum of 45 seconds

- 7.30** **When using water finding paste in heavy oils, which of the following actions should you take to enable the paste to be read more easily?**
- a. Gently blowing on the gauging bar to remove the heavy oil.
 - b. Use a soft cotton rag or towel to remove the excess oil
 - * c. Use a suitable solvent to gently wash to the surface of the paste.
 - d. Immerse the gauging bar in a container full of light product such as gasoline.
- 7.31** **To try to ensure gauging accuracy in shore tanks, what is the minimum recommended number of dips/gauges?**
- a. 1
 - * b. 2 identical dips out of three
 - c. 3 identical dips out of 4
 - d. 4 dips, averaged
- 7.32** **For what reasons may a quantity of free water (water bottoms) be maintained within a shore tank?**
- a. To permit easy determination of the shore tank free water quantity.
 - b. So that a certain percentage of free water can be pumped with each movement in order to aid in S&W blending of cargoes.
 - * c. To negate any effect that bottom flexing of the tank bottom would have on tank measured quantities.
 - d. To aid in detection of any product seepage from the tank.
- 7.33** **The use of non-slotted standpipes is not recommended for custody transfer measurements.**
- * a. True
 - b. False
 - c.
 - d.

7.34 When gauging a terminal storage tank prior to loading a barge, an inspector notes that his observed gauge height does not match the reference gauge height. On gauging the same tank on completion of loading the barge he again observes the same difference in observed and reference gauge heights, such that both opening and closing observed gauge height readings are identical. Can the gauges obtained be used for determining the loaded volume?

- * a. Yes
- b. No
- c.
- d.

7.35 When gauging a tank by the innage method, a comparison between the observed and reference gauge height is made to ensure which of the following?

- a. The gauge tape and bob are suspended in a vertical position within the tank.
- b. The gauge bob is in contact with the tank bottom or datum plate
- c. The tape has not been lowered too far into the tank
- * d. Answers a., b. and c. are all correct

7.36 When gauging a shore tank the tape should be read to the nearest 6mm [1/4 inch]?

- a. True
- * b. False
- c.
- d.

7.37 Can accurate volumes be obtained by gauging a tank while the roof is in the critical zone?

- a. Yes, when the tank legs are on low setting
- b. Yes, when the tank legs are on high setting
- * c. No, it cannot be done
- d. No, unless it is an internal floating roof

- 7.38** **If there is a discrepancy between Reference Gauge Height and Observed Gauge Height when gauging a shore tank what action should be taken?**
- a. Adjust the gauge to observed reference height
 - b. Ullage the tank
 - * c. Recheck the gauge, make a note of the difference and inform your supervisor
 - d. The difference can be ignored it as long as the ship to shore difference does not exceed 0.5%
- 7.39** **When inspecting Heavy Fuel Oil is it necessary to check for free water?**
- * a. Yes
 - b. No
 - c.
 - d.
- 7.40** **If the density of a product within a tank is greater than the density of water, where would any free water in this tank be found?**
- a. No free water would be found it as it would not settle out of this product but would remain in suspension
 - * b. On top of the product
 - c. Below the product
 - d. Answers a., b. and c. are all wrong
- 7.41** **According to common industry practice, how often must a gauging tape be checked for accuracy by comparison against a traceable master tape?**
- a. Prior to each use
 - b. Every six months
 - * c. Prior to initial use and at least annually
 - d. At least once per week

- 7.42** **How often should a working gauge tape be inspected for 'wear and tear'?**
- * a. Daily or prior to each use
 - b. Once per week
 - c. Once per month
 - d. Once per year
- 7.43** **Which of the following statements regarding reference gauge heights is correct?**
- a. They should be recorded from the calibration tables, before you start the tank gauging
 - b. They should be checked against the observed gauge heights
 - c. They should be included in the inspection report
 - * d. Answers a., b. and c. are all correct
- 7.44** **How are free water measurements normally taken?**
- * a. By the innage method
 - b. By the ullage method
 - c. By the Heimlich method
 - d. Answers a. and b. are correct
- 7.45** **When would a check be made for water on the top of a cargo?**
- a. If the observed density is less 1000 kg/m³ [observed API gravity greater than 10.0]
 - * b. If the observed density is greater 1000 kg/m³ [observed API gravity less than 10.0]
 - c. It is never necessary to check for the presence of water on top of a cargo
 - d. Only for fuel oil cargoes
- 7.46** **Which of the following is acceptable for the determination of free water for marine vessel custody transfer measurements?**
- a. A zone sampler
 - b. A portable measurement unit (PMU)
 - c. A bob with water-finding paste
 - * d. Answers b. and c. are correct

- 7.47** **If during gauging, the water cut falls on the clip of the gauge tape, what must be done?**
- a. Repeat the water cut measurement using a water bar
 - b. Repeat the water cut taking an ullage of the water
 - c. Interpolate the cut
 - * d. Answers a. and b. are correct
- 7.48** **What is the minimum amount of time the bob should stay in position while water cutting a heavy crude oil?**
- a. 10 seconds
 - b. 30 seconds
 - * c. 60 seconds
 - d. There is no set time
- 7.49** **When is a 'provisional gauge' or 'insurance gauge' taken prior to the 'official gauge'?**
- * a. When the 'official gauge' will not be taken for a significant period of time after completion of cargo operations.
 - b. When it is required by your employer's insurance company
 - c. When it is required by the Charter Party
 - d. Answers a., b. and c. are all correct
- 7.50** **What is one of the problems with water finding paste?**
- a. It tends to freeze in cold weather
 - * b. It does not perform consistently with all crudes
 - c. Tends to run down the bob
 - d. It is easily confused with gasoline paste
- 7.51** **If a tank's capacity table is an innage or dip table, what is the preferred method of gauging?**
- a. Side Gauge
 - b. Ullage
 - * c. Innage or dip
 - d. Outage

- 7.52 What do slip-tube gauging devices on rail tank cars measure?**
- a. Any liquid in the tank car deeper than 75 mm [3"]
 - * b. Any liquid under positive pressure in a tank car
 - c. Any vapour in a tank car
 - d. Any vapour with a depth greater than 1.2 m [4 feet]
- 7.53 When inspecting a series of rail tank cars the liquid outage/ullage level must be measured in all cars**
- * a. True
 - b. False
 - c.
 - d.
- 7.54 The floating roof of a shore tank displaces a certain volume of liquid when it is floating freely. What is the weight of the volume of liquid displaced equal to?**
- * a. The weight of the roof and attached deadwood
 - b. The weight of the roof less the attached deadwood
 - c. The weight of the roof adjusted for the density of the tank contents
 - d. Answers a., b. and c. are all wrong
- 7.55 What is the purpose of a floating roof correction in a shore tank calculation?**
- a. To account for the compression of the liquid due to the roof weight
 - * b. To account for the volume of liquid displaced as a result of the weight of the roof
 - c. To allow for the effect of the roof temperature on the temperature of the product
 - d. To allow for the effect of the temperature on the thickness of the roof

- 7.56 What action should an inspector take when requested to set a stop gauge?**
- a. Refuse, it's not an inspector's responsibility
 - * b. Follow the company's procedure
 - c. Set the stop gauge and take full responsibility
 - d. Tell the vessel/terminal personnel to set the stop and then check it for accuracy
- 7.57 When setting a min/max stop gauge an inspector should:**
- a. Make calculations and provide the gauge closest to the requested volume
 - b. Inspector's don't set stop gauges
 - c. Tell the terminal to set the stop and you will check it for accuracy
 - * d. Make calculations and provide the gauge closest to the requested volume without exceeding the volume to be transferred
- 7.58 Should the levels of H₂S vapor in tank headspace be declared or measured to be of 500 ppm or more, gauging may be performed only with closed UTIs; however, if the personal H₂S alarms are activated, then all work should stop.**
- * a. True
 - b. False

SECTION 8 – TEMPERATURE MEASUREMENT

- 8.01** **API MPMS Chapter 7/ISO 4268 pertains to what type of thermometers?**
- a. Mercury-in-glass
 - b. Alcohol-in-glass
 - c. Portable electronic thermometers
 - * d. Answers a., b. and c. are all correct
- 8.02** **Does API MPMS Chapter 7/ISO 4268 make any references to the construction of portable electronic thermometers?**
- * a. Yes
 - b. No
 - c.
 - d.
- 8.03** **Is a portable electronic thermometer required to have a low voltage indicator?**
- * a. Yes
 - b. No
 - c.
 - d.
- 8.04** **Why do portable electronic thermometers have low-voltage indicators?**
- a. So that it will not fail half way through the inspection
 - * b. The unit could give false readings if the battery is low
 - c. If the voltage drops, the night-light will not work
 - d. Most portable electronic thermometers do not have an indicator
- 8.05** **How does calibration of a portable electronic thermometer differ from a field check/verification?**
- a. It is done by the responsible manager
 - b. It is performed by a certified third party auditor
 - * c. It is verified in controlled conditions against a standard thermometer traceable to national standards
 - d. There is no difference between the two

- 8.06 On a portable electronic thermometer, what should be checked at least once per month?**
- a. The junction between the cable and the probe for mechanical damage
 - b. The cable insulation for cuts, breaks, or abrasion.
 - c. Two or more temperatures near the ends of the range of the probe
 - * d. Answers a., b. and c. are all correct
- 8.07 When verifying a portable electronic thermometer what is the maximum allowable tolerance versus reference standard thermometer?**
- * a. $\pm 0.25\text{ }^{\circ}\text{C}$ [0.5°F]
 - b. $\pm 0.05\text{ }^{\circ}\text{C}$ [0.1°F]
 - c. $\pm 1.0\text{ }^{\circ}\text{C}$ [2.0°F]
 - d. Answers a., b. and c. are all wrong - it must be exact
- 8.08 To what precision should temperatures obtained using portable electronic thermometers be read and recorded?**
- * a. To the nearest $0.1\text{ }^{\circ}\text{F}$ or $^{\circ}\text{C}$
 - b. To the nearest $0.5\text{ }^{\circ}\text{F}$ or $^{\circ}\text{C}$
 - c. To the nearest $1.0\text{ }^{\circ}\text{F}$ or $^{\circ}\text{C}$
 - d. To the nearest $1.5\text{ }^{\circ}\text{F}$ or $^{\circ}\text{C}$
- 8.09 What is the minimum acceptable accuracy for a portable electronic thermometer when it is indicating a temperature reading of $101\text{ }^{\circ}\text{C}$ [215°F]?**
- a. $\pm 1.0\text{ }^{\circ}\text{C}$ [2.0°F]
 - b. $\pm 0.5\text{ }^{\circ}\text{C}$ [1.0°F]
 - * c. $\pm 0.3\text{ }^{\circ}\text{C}$ [0.5°F]
 - d. $\pm 0.75\text{ }^{\circ}\text{C}$ [1.5°F]
- 8.10 To what increment should the display of a portable electronic thermometer be capable of reading?**
- a. $0.5\text{ }^{\circ}\text{F}$ or $^{\circ}\text{C}$
 - * b. $0.1\text{ }^{\circ}\text{F}$ or $^{\circ}\text{C}$
 - c. $1.0\text{ }^{\circ}\text{F}$ or $^{\circ}\text{C}$
 - d. $0.25\text{ }^{\circ}\text{F}$ or $^{\circ}\text{C}$

8.11 Which standards address the earthing (grounding) of portable electronic thermometers?

- * a. API MPMS Chapter 7.2/ISO 4268
- b. API MPMS Chapter 3/EI HM4
- c. API MPMS Chapter 8.1/ISO 3170
- d. API MPMS Chapter 17.9/EI HM49

8.12 If a portable electronic thermometer has a range of 0 - 100 °C [0-200°F], what is the required resolution?

- a. $\pm 1^{\circ}\text{C}$ [2°F]
- b. $\pm 0.2^{\circ}\text{C}$ [0.4°F]
- * c. $\pm 0.1^{\circ}\text{C}$ [0.2°F]
- d. Answers a., b. and c. are all wrong

8.13 Upright cylindrical storage tanks have calibration tables based on a specific tank shell temperature. If the observed tank shell temperature differs from the calibration table tank temperature will the volumes extracted from the calibration table will need to be corrected for this temperature difference?

- * a. Yes
- b. No
- c.
- d.

8.14 When using a liquid-in-glass thermometer it is important to consider that

- a. It should remain in the oil long enough to reach the temperature of the liquid
- b. It takes longer to obtain temperatures with a liquid in glass thermometer than a portable electronic thermometer
- c. It should be lowered using a gauging tape
- * d. Answers a. and b are correct

- 8.15** **What information must be recorded when taking a temperature of a cargo using an in-line probe ?**
- a. The last calibration date
 - b. The serial number of the unit being used.
 - * c. The last two times the probe was checked for accuracy
 - d. Answers a., b. and c. are all wrong
- 8.16** **What must be done immediately before taking temperatures using a portable electronic thermometer?**
- a. Set the temperature range selector.
 - b. Earth (ground) the unit, after opening the gauge hatch or vapour control valve
 - c. Check the battery for low voltage
 - * d. Earth (ground) the unit, before opening the gauge hatch or vapour control valve
- 8.17** **If a tank has more than 6 m [20 feet] of liquid, what is the minimum number of temperature readings that must be taken?**
- * a. 3
 - b. 5
 - c. 1
 - d. one every 1 m [3 feet]
- 8.18** **If only one temperature is required where should this temperature be taken from?**
- a. The middle of the upper third
 - * b. The middle of the liquid level
 - c. The middle of the lower third.
 - d. Use a side readout thermometer

- 8.19 The quickest way to stabilize the reading from a portable electronic thermometer (PET) is to?**
- a. Allow the probe to stay in the product for twice the required time
 - * b. Move the probe up and down at least 30 cm [1 foot] above and below the spot the temperature is to be taken
 - c. Use fresh batteries
 - d. There is no way to speed up the stabilization process
- 8.20 What is the minimum amount of product needed for a temperature to be taken?**
- * a. Whenever there is sufficient material present to immerse the probe
 - b. 30 cm [1 foot]
 - c. One metre [3 feet]
 - d. Temperatures should only be taken when the roof is floating freely
- 8.21 To what increment should a portable electronic thermometer be read and recorded?**
- a. The nearest 0.5°C or °F
 - b. The nearest 1°C or °F
 - * c. The nearest 0.1°C or °F
 - d. Answers a.,b. and c. are all wrong.
- 8.22 According to common industry practice how should the working spot check (field check) of a portable electronic thermometer be performed?**
- a. Daily comparison to another portable electronic thermometer
 - * b. By comparing it to a reference standard thermometer before each use or once per day, whichever is less frequent
 - c. By checking the unit weekly, for accuracy
 - d. Calibrate against a thermometer (traceable to national standards) at prescribed intervals

- 8.23** **Liquid-in-glass thermometers are suitable for use in obtaining cargo product temperatures in marine vessels required to operate with closed or restricted systems?**
- a. True
 - * b. False
 - c.
 - d.
- 8.24** **According to ISO 4268 [API Chapter 7.2] the minimum amount of time a stationary PET should stay in a product with a density greater than 935 kg/m³ is ?**
- a. 10 minutes
 - b. 1 minute
 - c. 5 minutes
 - * d. Until the readout doesn't vary by more than 0.1°C [0.2°F] for 30 seconds
- 8.25** **According to API MPMS Chapter 7.2 the minimum amount of time that an 'in motion' probe should stay in a product with an API gravity less than 20 is?**
- a. 80 minutes
 - b. 30 minutes
 - * c. 75 seconds
 - d. 10 seconds
- 8.26** **If a tank has an innage of 2,8m [9' 11"] what is the minimum number of temperatures which should be taken?**
- * a. One
 - b. Two
 - c. Three
 - d. None

8.27 On a portable electronic thermometer, at what temperature should the field check be performed ?

- a. 0°C [32°F]
- b. 100°C [212°F]
- * c. Ambient temperature
- d. Expected cargo temperature

8.28 When using a portable electronic thermometer what is an indication of temperature stabilization?

- a. Comparison with the side temperature on the tank
- b. Comparison with a cup-case thermometer
- c. Comparison with the last temperature recorded by the terminal
- * d. Readout doesn't vary by more than 0.1°C [0.2°F] for 30 seconds

8.29 What is the minimum number of temperatures to be taken on a marine vessel with tanks containing less than 3m [10 feet] of product?

- * a. One per tank
- b. Three per tank
- c. Weighted average per tank
- d. Answers a., b. and c. are all wrong

8.30 API MPMS Chapter 7 describes a "large temperature difference" between upper, middle and lower reading as?

- a. Greater than 0.5°F [0.25°C]
- b. Greater than 1.0°F [2.0°C]
- * c. Greater than 2.0°F [1.0°C]
- d. Greater than 5°F [2.5°C]

8.31 What is the maximum amount by which the reading on a portable electronic thermometer can vary when it may be considered to have stabilized?

- a. 0.3 °C [0.5°F]
- b. 1 °C [2.0°F]
- c. No variation is permitted
- * d. 0.1 °C [0.2°F]

- 8.32** When taking temperatures for ROB, OBQ or slops containing oil and water it is important _____
- a. That the probe doesn't touch the steam coils
 - b. That the tank is corrected for list / trim
 - * c. That the probe is placed at the mid-point of the oil or the oily layer
 - d. That only a middle temperature is taken for slops
- 8.33** When using a portable electronic thermometer, what is the minimum amount of time the probe must stay in a middle distillate of density 821.7 kg/m³ [API gravity 40.7] , if the probe is moving?
- * a. 30 seconds
 - b. 1 minute
 - c. 2 minutes
 - d. 5 minutes
- 8.34** A thermowell used to measure temperature must be filled with a suitable heat-transfer liquid.
- * a. True
 - b. False
 - c.
 - d.
- 8.35** Which ISO standard covers manual temperature determination?
- a. ISO 3171
 - * b. ISO 4268
 - c. ISO 4512
 - d. ISO 4266
- 8.36** A liquid-in-glass thermometer with a range between 60°F and 180°F and must be accurate to within?
- a. ± 1.0 °F
 - * b. ± 0.5 °F
 - c. ± 0.1 °F
 - d. ± 0.25 °F

- 8.37 Which API MPMS Chapter covers temperature determination?**
- a. Chapter 3
 - * b. Chapter 7
 - c. Chapter 8
 - d. Chapter 17
- 8.38 How should scale graduation marks be applied to a liquid-in-glass thermometer?**
- * a. They must be etched permanently on the stem of the thermometer
 - b. They must be etched permanently on the cup-case assembly
 - c. They must be on a metal plate attached to either the thermometer or the cup-case assembly
 - d. Answer a., b. or c. is correct
- 8.39 An ASTM 59C [ASTM 59F-80] liquid-in-glass thermometer has a scale range of -18°C to 82°C [0°F-180°F]. What should the graduations on this thermometer be?**
- a. 0.1°C [0.2°F]
 - b. 0.25°C [0.5°F]
 - c. 1.0°C [2.0°F]
 - * d. 0.5°C [1.0°F]
- 8.40 When first received from the manufacturer or equipment supplier, what should happen to a new liquid-in-glass tank thermometer?**
- a. It can be used immediately because the manufacturer calibrates the thermometer before it is shipped
 - b. It must be checked to see that the liquid column is intact, then it may be used since the manufacturer will have calibrated the thermometer.
 - c. It must be checked to see that the glass stem is not cracked or broken, then it may be used since the manufacturer will have calibrated the thermometer
 - * d. It must be compared against a thermometer certified by a National Standard body or an equivalent thermometer of traceable accuracy.
-

- 8.41** **A liquid-in-glass thermometer must be verified against a thermometer traceable to a national standard when new and then at maximum intervals of?**
- a. 3 months
 - b. 6 months
 - * c. 1 year
 - d. 5 years
- 8.42** **'In motion' is defined as continuously raising and lowering the probe above and below the desired temperature measurement depth, by approximately how much?**
- a. 15cm [6 inches]
 - b. 1metre [40 inches]
 - * c. 30cm [12 inches]
 - d. 50cm [20 inches]
- 8.43** **What does the term 'temperature stratification' mean?**
- a. That there are differences in temperature at different distances from the tank wall (tank shell)
 - b. That there are differences in temperature at different levels in a tank
 - c. That the temperature difference measured at any two levels in a tank exceeds 2 °C [5°F]
 - * d. Answers a. and b. are correct
- 8.44** **When using a liquid-in-glass thermometer in a cup-case assembly to measure a product with density of 904 kg/m³ [API gravity 24.9] what is the minimum length of time the thermometer should be immersed in the liquid when the assembly is in motion during the measurement process?**
- a. 5 minutes
 - b. 10 minutes
 - * c. 20 minutes
 - d. Until the readout doesn't vary by more than 0.2 °C for 30 seconds

- 8.45** What is the minimum number of temperatures to be taken in a tank containing less than 3m [10 feet] of product?
- * a. 1
 - b. 3
 - c. 5
 - d. 2
- 8.46** When taking the temperature of a product in a tank and there is more than 1°C [2 °F] difference between upper, middle and lower temperatures, what steps should be taken?
- a. Retake the temperatures since there must be an error
 - b. Use the middle temperature only for the entire tank contents
 - c. Average the upper, middle and lower temperatures
 - * d. Take temperatures at more frequent, equally-spaced vertical increments
- 8.47** When taking temperatures, 'in motion' means to move the temperature measurement device approximately 60cm [2 feet] above and 60cm [2 feet] below the desired measurement location?
- a. True
 - * b. False
 - c.
 - d.
- 8.48** What is the recommended immersion time, for a liquid-in-glass thermometer in a cup-case assembly, in motion, in a product with density of 950 kg/m³ [API gravity 17.4]
- * a. 45 minutes
 - b. 10 minutes
 - c. 20 minutes
 - d. Until the readout doesn't vary by more than 3.0 °C for 30 seconds

- 8.49** **What temperature is to be used during an ROB survey if there is only 5 cm [2 inches] of liquid in the bottom of the tank?**
- a. The measured temperature at the middle of the liquid
 - * b. Standard Temperature
 - c. The average temperature of the product in the tank before it was discharged
 - d. The temperature stated by the vessel's representative
- 8.50** **A 4 000m³ [25 000bbl] capacity storage tank has a depth of product of 4.70 m [15 feet] in the tank. What is the minimum number of temperature measurements that should be obtained on this tank.**
- a. One
 - * b. Two
 - c. Three
 - d. Five
- 8.51** **The immersion time for a cup-case assembly is minimized by continually raising and lowering the assembly 0.3m [1 foot] above and below the desired temperature measurement point.**
- * a. True
 - b. False
 - c.
 - d.
- 8.52** **What procedure is used to field check a liquid-in-glass thermometer in a cupcase assembly?**
- a. It is checked against a portable electronic thermometer
 - b. It is checked it against the ship's thermometer
 - * c. it is checked for cracks, cleanliness and a readable scale and the liquid column is checked as unbroken
 - d. It is placed in a 100°F water bath with a certified thermometer for 45 minutes and compare the readings. They must be within 0.2°C [0.1°F]

8.53 What is the purpose of keeping the probe of a portable electronic thermometer (PET) in motion?

- a. To ensure the unit is calibrated
- b. To stir the product
- * c. To minimize temperature stabilization time
- d. To prevent the probe becoming 'caught up' in the tank ladder

8.54 According to API MPMS Chapter 17.1, the preferred instrument for taking temperature is?

- a. A liquid-in-glass thermometer
- * b. A portable electronic thermometer
- c. An in-line temperature probe
- d. A preferred instrument is not specified

SECTION 9 - METERING

- 9.01 When correcting a metered volume from line conditions to standard conditions manually which of the following corrections need to be applied?**
- a. Pressure and temperature corrections for the liquid
 - b. Pressure and temperature corrections for the meter body
 - c. No corrections are necessary if the meter is calibrated
 - * d. Corrections a. and b. must be applied
- 9.02 When calculating standard volume from a raw meter output which of the following corrections need to be applied?**
- a. Pressure and temperature corrections for the liquid
 - b. Pressure and temperature corrections for the meter body
 - * c. Corrections a. and b. and a meter factor
 - d. Corrections a. and b. only
- 9.03 How should a meter be proved?**
- a. By comparing meter readings with shore tank measurements
 - b. By comparing meter readings with Total Received Volume (TRV) on-board ship
 - * c. Using a prover loop
 - d. By comparison against the next meter in the 'meter bank'
- 9.04 What is the minimum number of sphere detectors which are used on a uni-directional pipe prover?**
- * a. 2
 - b. 4
 - c. 3
 - d. 1

9.05 Under what conditions should a meter factor remain constant?

- * a. Different flow rates
- b. Different products
- c. Under conditions a. and b.
- d. All transfers between successive calibrations

9.06 Which API Chapter contains compressibility factors for use when calculating metered volumes?

- a. Chapter 11.5
- * b. Chapter 11.2
- c. Chapter 12.1
- d. Chapter 12.2

SECTION 10 - ETHICS

- 10.01 Which of the following actions represents an ethical problem for an Inspector?**
- a. Correcting the temperature of a shore tank when the PET has been found to be inaccurate
 - b. Changing the VCF after finding an error in the API gravity of the cargo
 - * c. Changing the temperature of the cargo in a ship's tank because it is too far off the shore tank temperature
 - d. Answers a., b. and c. are all correct
- 10.02 The liquid level of a shore tank is changed in the raw data book after it is found to be wrong upon re-gauging. The original data is covered with white-out fluid and the correct information is written over the blanked-out data. Is this a permissible way to handle raw data corrections?**
- a. Yes
 - * b. No
 - c.
 - d.
- 10.03 The key person involved in managing ethics concerns in an inspection company would usually be the Compliance Officer.**
- * a. True
 - b. False
 - c.
 - d.

- 10.04** **When inspecting a petroleum or chemical cargo, which of the following represents sound ethical business conduct for an Inspector?**
- a. Making sure that the Inspector's results match the results required by the customer
 - * b. Making sure that the job is done according to industry standards
 - c. Making sure that the laboratory gets their sample on time
 - d. Answers a., b. and c. are all correct
- 10.05** **Which procedure is acceptable when raw data, such as dips or temperatures, must be corrected?**
- a. White out the original measurements and write the correct measurements clearly over the blanked-out area
 - * b. Draw a single line through the original measurements so they can still be read and rewrite the correct measurements on the next line.
 - c. Tear the original page out of the raw data book or pad and start again
 - d. Answers a., b. and c. are all wrong
- 10.06** **The Compliance Programme established by your Company requires that you comply with national regulations issued by:**
- a. Agencies for the Environment, Food and Agriculture
 - b. Customs and Excise authorities
 - c. Agencies for Occupational Health and Safety
 - * d. Answers a., b. and c. are all correct
- 10.07** **'Zero Tolerance' means that any and all infractions of your Company's Regulatory Compliance Program are subject to disciplinary action.**
- * a. True
 - b. False
 - c.
 - d.

- 10.08** **TIC Council Member Companies strictly prohibit any form of retaliation against any person who, in good faith, files a complaint under their Regulatory Compliance Program, or assists in a Program violation investigation.**
- * a. a. True
 b. b. False
 c.
 d.
- 10.09** **Changes to raw data cannot be made without a sound technical justification or re-measurement.**
- * a. True
 b. False
 c.
 d.
- 10.10** **Reported data must be backed by, and be identical to its recorded data.**
- * a. True
 b. False
 c.
 d.
- 10.11** **It is acceptable to alter analytical results based solely upon repeatability provided that the new result falls within the precision limits of the test method.**
- * a. True
 b. False
 c.
 d.

- 10.12** It is acceptable to ignore a potential violation of your Company's Regulatory Compliance Program if the violation does not directly involve you.
- a. True
 - * b. False
 - c.
 - d.
- 10.13** On finishing the closing inspection on a shore tank, following the completion of a marine vessel discharge operation, a representative who is witnessing your actions requests that you change the observed tank product temperature reading obtained as he feels that it is incorrect. What should you do?
- a. Comply with his wishes
 - b. Use the observed temperature of the product on the vessel prior to discharge
 - * c. Inform him that you will re-check the product temperature if he requires but that you will record and use the product temperature that you have observed
 - d. Use the tank auto temperature reading instead
- 10.14** A client loss control representative repeatedly attempts to have gauges recorded as being slightly more than measured. What action should be taken?
- a. Comply with the request
 - b. Politely refuse to change any gauges
 - c. Report the requests to your office
 - * d. Answers b. and c. are correct
- 10.15** When a loss control representative is witnessing gauges he/she has the authority to ask the inspector to make judgement calls in their favor?
- a. True
 - * b. False
 - c.
 - d.

10.16 **While gauging ROB's with the vessel's officer and a loss control representative the measurement is 2.5cm. However, the vessel's officer argues it should be 2cm and the loss control representative says it should be 3cm. What should be done ?**

- a. Repeat the measurement until they are both satisfied.
- * b. They should be informed that the official measurement is the one taken by the independent inspector. This should be recorded and work should move on to the next tank
- c. The inspector is not a referee and should use a cell phone and call his/her supervisor.
- d. None of the above

10.17 **While sampling a bottle is lost from your sampling device and it's now somewhere in the tank. What action should be taken?**

- a. Another bottle should be used and no other action taken
- * b. The representative of the tank/vessel should be advised together with the inspector's supervisor
- c. The representative of the tank/vessel should be advised and any papers provided by the representative should be signed
- d. Attempts should be made to retrieve the bottle from the tank

- 10.18** **When it is not possible to carry out an inspection according to the relevant standards or the instructions which have been provided, what action should an inspector take?**
- a. Carry out the work to the best of his/her abilities, using experience to estimate any missing measurements or overcome any restrictions.
 - b. Continue with the inspection but remove those parts where standards or instructions cannot be followed.
 - * c. Advise the his/her supervisor of the problem so that the client can be informed and alternative procedures agreed.
 - d. Exercise a Stop Work Authority
- 10.19** **Owners or operators of a site or vessel occasionally request that inspectors sign waivers relieving them from their legal obligation to provide a safe place of work. It is TIC Council policy that inspectors should not be required to sign any document which waives their rights as individuals or as employees under the law.**
- * a. True
 - b. False
 - c.
 - d.
- 10.20** **The TIC Council Code of Practice discusses:**
- a. Health Safety and the Environment
 - b. Training
 - c. Nomination and acknowledgement
 - * d. All the above answers are correct

- 10.21** **TIC Council training requirements are referred to in the Code of Practice and include:**
- * a. Technical skills, Health, Safety and Environment, and Communications
 - b. There are no specific requirements
 - c. Customer specific site training
 - d. Answers a. and c. are correct
- 10.22** **In accordance with the TIC Council Code of Practice, inspectors may only countersign third party Tank Inspection Certificates or Reports with an approved disclaimer provided by their company.**
- * a. True
 - b. False
 - c.
 - d.
- 10.23** **What action should be taken if the chief officer provides different instructions from those received from the client?**
- a. Vessel's instructions should be followed
 - b. The clients's instructions should be followed
 - * c. Advise the client immediately
 - d. Agree a solution with the Master
- 10.24** **Who is responsible for control and custody of a cargo during an offshore ship to ship operation?**
- a. The inspector
 - b. The terminal
 - * c. The vessels
 - d. The agent

- 10.25 What should an inspector do if asked to sign indemnities on behalf of their employer relieving the owner or operator of a site or vessel from their legal obligation to provide a safe place of work?**
- a. Always sign the indemnity and proceed to perform the job
 - b. Refuse to sign the indemnity and leave the work site
 - * c. Advise their supervisor immediately and refuse to sign the indemnity
 - d. Sign the indemnity with appropriate disclaimer

BACK COVER